

बिड दस्तावेज़ / Bid Document

बिड विवरण / Bid Details	
बिड बंद होने की तारीख/समय / Bid End Date/Time	19-03-2026 18:00:00
बिड खुलने की तारीख/समय / Bid Opening Date/Time	19-03-2026 18:30:00
बिड पेशकश वैधता (बंद होने की तारीख से) / Bid Offer Validity (From End Date)	90 (Days)
मंत्रालय/राज्य का नाम / Ministry/State Name	Ministry Of Home Affairs
विभाग का नाम / Department Name	Central Armed Police Forces
संगठन का नाम / Organisation Name	National Security Guard (nsg)
कार्यालय का नाम / Office Name	Directorate General
कुल मात्रा / Total Quantity	23455
	PVC Pendent Holder. , One way. Bed switch. , Single pole 10 amps, two way switch, ISI marked. Modular type. , Modular Bell Push Switch. , Modular blanking plate. , Single pole 25 amps, one way modular switch, ISI marked. , 2 module, Modular base and cover plate. , 3 module, Modular base and cover plate. , 4 module, Modular base and cover plate. , 6 module, Modular base and cover plate. , 12 module, Modular base and cover plate. , Flame Retardant, PVC Electrical insulation Tapes 6 mtr X 1.8 cm long. , PVC gitt, PVC rawal plug, PVC fastener 38 to 40mm long. , 3 mm thick phenolic laminated sheet. , 1.5 Sq. mm. FRLS or HFFR single core, multi strand copper conductor, PVC insulated cable suitable upto 1100 volts. , 4.0 Sq. mm. FRLS or HFFR single core, multi strand copper conductor, PVC insulated cable suitable upto 1100 volts. , 6.0 Sq. mm. FRLS or HFFR single core, multi strand copper conductor, PVC insulated cable suitable upto 1100 volts. , Modular MCB single pole 25 Amp C curve, 3 kA breaking capacity. , Pin Anchor Fastener 6 x 50 , Pin Anchor Fastener 8 x 50 , Pin Anchor Fastener 8 x 75 , Pin Anchor Fastener 10 x 100 , Ring Hook Fastener M-8 , Ring Hook Fastener M-10 , Wedge Anchor Fastener 8 mm x 75 mm , 3 mm thick PVC or phenolic laminated round sheet cover minimum 170 mm dia for fan box. , 3 mm thick PVC or phenolic laminated round sheet cover 100 mm dia. , 3 module , PVC Surface Modular box for following module. , 6 module , PVC Surface Modular box for following module. , BEE 5 star rating, 25 litres capacity water storage heater, with protection against over heating, Multifunction Safety Valve and external adjustable thermostat. , 1200 mm sweep, BEE 5 star rated, ceiling fan with Brush Less Direct Current Motor. , Supply of 400 MM, Single phase wall mounting fan. , Fresh air fan with louver shutter 250 mm sweep. , 230 mm sweep, 1400 RPM , single phase, metallic

बिड विवरण / Bid Details	वस्तु श्रेणी / Item Category
	<p>exhaust fan Conforming to IS 2312 -1967. , Metallic louvred shutter suitable for 300 mm sizes exhaust fan. , Metallic louvred shutter suitable for 380 mm sizes exhaust fan. , 18-22 watt LED surface mounted Batten light. , 40 watt LED surface mounted Batten light. , 5-7 watt LED Recessed or surface Down lighter. , 12 -15 watt LED Recessed or surface Down lighter. , 18 watt LED Recessed or surface Down lighter. , LED Batten Emergency ,Inverter, luminaire minimum system lumen output of 2000 lumen. , Utility knife Tapaia UK-3 , Spare Blade UB-10 for utility knife UK-3 Taparia , Flexible connection pipe 450mm Long, metal braided Hoses . , Measuring Tape, Length of the Tape is 30 M. The width of the Blade is 13mm. , Casing Capping clip , PVC Nail Clip 20 mm Double Nail. , Aluminium Paint . , Red Oxide Metal Primer. , Paint Thinner. , Paint Brush 2 inch , Paint Brush 3 inch , Wooden Screw 35 x 8 , Wooden Screw 50 x 8 , Dry wall Gypsum Screw 0.75 inch , Dry wall Gypsum Screw 1inch , Dry wall Gypsum Screw 1.5 inch , 10 Amp, 12 way, PVC Strip Connector. , 15 Amp, 12 way, PVC Strip Connector. , Iron drill bit Set having 25 Pcs . , Self supported FRP Platform Step Ladder , Multifunction Testers . , 400 Amp 04 Pole Power contactor. , 16 Sq mm Aluminium Flat thimble , 25 Sq mm Aluminium Flat thimble , 50 Sq mm Aluminium Flat thimble , 70 Sq mm Aluminium Flat thimble , 95 Sq mm Aluminium Flat thimble , 120 sq mm Aluminium Flat thimble , 150 Sqmm Aluminium Flat thimble , 185 Sq mm Aluminium Flat thimble , 240 Sq mm Aluminium Flat thimble , 300 Sq mm Aluminium Flat thimble , 400 Sq mm Aluminium Flat thimble , 16 Sq mm Aluminium Ferrule , 25 Sq mm Aluminium Ferrule , 35 Sq mm Aluminium Ferrule , 50 Sq mm Aluminium Ferrule , 70 Sq mm Aluminium Ferrule , 70 watt Flood Light, powder coated pressure die cast aluminium body with driver . , 150 watt Flood Light, powder coated pressure die cast aluminium body with driver. , 45 watt Street light LED fixture powder coated pressure die cast aluminium body with driver . , 72 watt Street light LED fixture powder coated pressure die cast aluminium body with driver. , 90 watt Street light LED fixture powder coated pressure die cast aluminium body with driver. , 150 watt Street light LED fixture powder coated pressure die cast aluminium body with driver as per the requirement with Driver. , 10 to 11 Watt, 0.6 Metre nominal size LED Bollard Light fitting complete with LED module. , 25-watt LED-based post-top luminaire, IP 65, with Die-cast aluminium spigot housing, complete with diffuser, LED module, driver with surge protection . , 10 Watt to 12 Watt Spike LED light with aluminium housing, IP66 having tiltable feature to throw light in the desired direction. , Straight through cable jointing kit with heat shrinkable kit with ferrules for 1.1 KV grade cable. Size 2 X 16 sq. mm sq. mm 1.1 KV grade cable. , Straight through cable jointing kit with heat shrinkable kit with ferrules for 1.1 KV grade cable. Size 2 X 25 sq. mm sq. mm 1.1 KV grade cable. , Straight through cable jointing kit with heat shrinkable kit with ferrules for 1.1 KV grade cable. Size 3.5 X 35 sq. mm sq. mm 1.1 KV grade cable. , Straight through cable jointing kit with heat shrinkable kit with ferrules for 1.1 KV grade cable. Size 3.5 X 300 sq. mm 1.1 KV grade cable. , Cable Junction Boxes, IP 66 weather proof, size 205 mm x 255 mm x 112 mm, with terminals suitable for 16 sq mm cable. , 4 Inch Cutting Wheel for Metal suitable for 4 inch angle grinder. , 1.5 Volt Alkaline non-rechargeable, type battery, size- AAA. , 1.5 Volt Alkaline non-rechargeable, type battery, size- AA. , 9 Volts Alkaline non-rechargeable Battery. , 23A, 12V Alkaline Battery. , LED</p>

बिड विवरण / Bid Details	Rope Light, 10 watt per metre or 120 LED per metre, in various colors, IP65 rating, with adopter. , Supplying of Adapter for LED Rope Light. , LED Rope Light, 6 W per Mtr, IP65, Tri-Color. 18 Meter. , Supplying Pidilite WD 40 mechanical contact cleaner in 500 ml can with Straw Spray. , 2 x 16 sq mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade , confirming to IS 7098 Part 1 1988 with upto Date Amendments. , 2 x 25 sq mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade , confirming to IS 7098 Part 1 1988 with upto Date Amendments. , 3.5 x 35 sq. mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade, confirming to IS 7098 Part 1 1988 with up to Date Amendments. , 3.5 x 120 sq. mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade, confirming to IS 7098 Part 1 1988 with up to Date Amendments. , 3.5 x 400 sq. mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade, confirming to IS 7098 Part 1 1988 with up to Date Amendments. , Socket tester to verify that the wall socket is correctly wired and to check for common faults. , M-Seal - Regular epoxy compound. , Pu Foam Insulation Sealant 750 ml , Distilled Water, 5 Liters . , Weatherproof, IP66, wire connector with plug and socket suitable for 4 sq mm copper cable. , Digital Earth Resistance Tester. , PVC Weatherproof, IP65, 8 module MCB DB with DIN rail. , Wall-Mounted Voltage Stabilizer, Suitable for 1.5 Ton Split Air Conditioner. , Wall-Mounted Voltage Stabilizer, Suitable for 2 Ton Split Air Conditioner. , Blue Plastic Crate, 4 Litre Capacity, Size 300 x 200 x 100 mm, suitable for material storage. , PVC Weatherproof Switch Box, IP66 Rated. , A Power adaptor with in built RCD 30 ma , Robustt Caution Tape 3 Inches x 130 Mt, Pack of 1, White and Red PVC Material, Barricade tape. , Polypropylene Floor Standing Caution Sign Board , Stainless Steel Clip for fixing LED batten as per sample provided by department. , Waterproof Paint Marke. , 15A insulated test lead cable with dual-ended insulated crocodile clips, suitable for electrical testing. Set of 5 Pc. , Plastic Step Stool, Nominal Dimensions Width 57 cm, Depth 54 cm, Height 60 cm. , 30W 220V Round Corded Soldering Iron with LED Worklight . 6 Months Warranty. , Solder Paste Flux Pack -50 gm , Lead-Free Soldering Wire, 0.8 mm diameter, suitable for electronic and electrical soldering and component repair. 20-gram pack. , Cleaning Cloth Towels, Material 100 percent cotton. , Microfiber Multi-Purpose Cleaning Wipe. , Contactless Surface Temperature Detector. , PVC Plastic Pipe Cutter, Cutting Capacity Up to 42 mm , HSS Bi-metal Holesaw Set, 20 TO 64 mm diameter hole saw sizes 20, 25, 32, 38, 51, and 64 mm. , Plastic Tool Box with Organizer, Height 150 mm, width 190 mm, length 335 mm , High carbon steel Shovel with Wooden Handle. , Hoe Powrahs , High Tempered Iron Pickaxe , Aluminium Self
	<p> 3000 Type One Way Switch, 240 v, 50 Hz, Single pole 10 amps, two way switch, ISI marked. Modular type, Modular Bell Push Switch. Modular type, Modular blanking plate, Single pole 25 amps, one way modular switch, ISI marked., 2 module, Modular base & cover plate, 3 module, Modular base & cover plate, 4 module, Modular base & cover plate, 6 module, Modular base & cover plate, 12 module, Modular base & cover plate, Flame - Retardant, PVC Electrical insulation Tapes 6 mtr X 1.8 cm long, PVC gitti / PVC rawal plug /PVC fastener 38/40mm long/PVC fastener 38/40mm long, 3 mm thick phenolic laminated </p>

बिड विवरण / Bid Details	sheet, 1.5 Sq. mm. FRLS / HFFR single core, multi strand copper conductor, PVC insulated cable suitable upto 1100 volts, 4 Sq. mm. FRLS / HFFR single core, multi strand copper conductor, PVC insulated cable suitable upto 1100 volts, 6.0 Sq. mm. FRLS/HFFR single core, multi strand copper conductor, PVC insulated cable suitable upto 1100 volts, Modular MCB single pole 25 Amp "C" curve, 3 kA breaking capacity., Pin Anchor Fastener 6 x 50, Pin Anchor Fastener 8 x 50, Pin Anchor Fastener 8 x 75, Pin Anchor Fastener 10 x 100, Ring Hook Fastener M-8, Ring Hook Fastener M-10, Wedge Anchor Fastener 8 mm x 75 mm, 3 mm thick PVC/ phenolic laminated round sheet cover minimum 170 mm dia for fan box., 3 mm thick PVC / phenolic laminated round sheet cover 100 mm dia., 3 module , PVC Surface Modular box, 6 module , PVC Surface Modular box, BEE 5 star rating, 25 litres capacity water storage heater, with protection against over heating, Multifunction Safety Valve and external adjustable thermostat, with 16 A, 240 V, plug top with in-built 30 mA RCD and 02 nos flexible connection pipe suitable for working with 230V AC, 50 Hz, 1 Phase supply etc as required. (with 7 year warranty on inner tank, 3 year warranty on heating element, 2 year comprehensive Warranty), 1200 mm sweep, BEE 5 star rated, ceiling fan with Brush Less Direct Current (BLDC) Motor, class of insulation B, 3 nos. blades, down rod upto 30 cm long , 2 nos. canopies, shackle kit, safety rope, copper winding, Power Factor not less than 0.9, Service Value (CMM/W) minimum 8.00, Air delivery minimum 215 CMM, 350 RPM (tolerance as per IS 374-2019), THD less than 10%, without remote and compatible with existing step electronic regulator unit for speed control and all remaining accessories including safety pin, nut bolts, washers, temperature rise 75 degree C (max.), insulation resistance more than 2 mega ohm, suitable for 230 V, 50 Hz, single phase AC Supply. The firm has to submit a type test report of the ceiling fan from a NABL accredited lab before commencement of supply. (BLDC Ceiling fan with minimum 2 years Warranty), Supply of 400 MM, Single phase wall mounting fan, Fresh air fan with louver shutter 250 mm sweep., 230 mm sweep, 1400 RPM , single phase, metallic exhaust fan Conforming to IS:2312 -1967., Metallic louvred shutter suitable for 300 mm sizes exhaust fan., Metallic louvred shutter suitable for 380 mm sizes exhaust fan., 18-22 watt LED surface mounted Batten light of following body material and construction as per IS : 10322 with driver (Replaceable) as per the requirement with Driver efficiency >85%, Operating voltage AC 140-270 Volt, frequency 50/60 hz, Operating temp range -5 °C to 40 °C, internal surge protection of 2.5 KV with Short & Open circuit protection ,THD < 10% , P. F. ≥ 0.95, IP20, CRI ≥ 80 , Flicker free (flicker should be below 5 %), life time (LED, Driver & electrical circuitry), of minimum 50000 Burning Hours with , 70% of initial Lumen maintained till life ends, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM(Standard Deviation Color Matching) <3, Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard. Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. with Minimum 5 year OEM warranty. System lumen efficacy ≥120 <135 lm/Watt output LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement.

बिड विवरण/Bid Details

(Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C). Powder coated die cast / Extruded aluminium Body (Thickness ≥ 1.20 mm), 40 watt LED surface mounted Batten light of following body material and construction as per IS : 10322 with driver (Replaceable) as per the requirement with Driver efficiency $>85\%$, Operating voltage AC 140-270 Volt, frequency 50/60 hz, Operating temp range -5 °C to 40 °C, internal surge protection of 2.5 KV with Short & Open circuit protection ,THD $< 10\%$, P. F. ≥ 0.95 , IP20, CRI ≥ 80 , Flicker free (flicker should be below 5 %), life time (LED, Driver & electrical circuitry), of minimum 50000 Burning Hours with , 70% of initial Lumen maintained till life ends, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM(Standard Deviation Color Matching) <3 , Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard. Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. with Minimum 5 year OEM warranty. System lumen efficacy $\geq 120 < 135$ lm/Watt output LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C). Powder coated die cast / Extruded aluminium Body (Thickness ≥ 1.20 mm), 5-7 watt LED Recessed/surface Down lighter (Round / square/ Rectangular) SMD type of following body material with PMMA and prismatic diffuser and construction as per IS : 10322 with driver as per the requirement with Driver efficiency $>85\%$, Operating voltage AC 140-270 Volt, frequency 50/60 hz, Operating temp range -5 °C to 40 °C, internal surge protection of 2.5 KV with Short & Open circuit protection ,THD $< 10\%$, P. F. ≥ 0.95 , IP20, CRI ≥ 80 , UGR (Unified Glare Rating) ≤ 19 Flicker free (flicker should be below 5 %), life time (LED, Driver & electrical circuitry), of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends, as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM (Standard Deviation Color Matching) <3 , Maximum power consumption should not more than the specified rating and Fixture shall be to relevant BIS standard. Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. Complete in all respect with Minimum 5 year OEM warranty. System lumen efficacy $\geq 120 < 135$ lm/Watt output. LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C) Powder coated die cast /Extruded aluminium Body including trim., 12 -15 watt LED Recessed/surface Down lighter (Round / square/ Rectangular) SMD type of following body material with PMMA and prismatic diffuser and construction as per IS : 10322 with driver as per the requirement with Driver efficiency $>85\%$, Operating voltage AC 140-270 Volt, frequency 50/60 hz, Operating temp range -5 °C to 40 °C, internal surge protection of 2.5 KV with Short & Open circuit protection ,THD $< 10\%$, P. F. ≥ 0.95 , IP20, CRI ≥ 80 , UGR (Unified Glare Rating) ≤ 19 Flicker free (flicker should be below 5 %), life time (LED, Driver & electrical circuitry), of minimum 50000 Burning Hours with 70% of

बिड विवरण / Bid Details

initial Lumen maintained till life ends, as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM (Standard Deviation Color Matching) <3, Maximum power consumption should not more than the specified rating and Fixture shall be to relevant BIS standard. Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. Complete in all respect with Minimum 5 year OEM warranty. System lumen efficacy $\geq 120 < 135$ lm/Watt output. LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C) Powder coated die cast /Extruded aluminium Body including trim., 18 watt LED Recessed/surface Down lighter (Round / square/ Rectangular) SMD type of following body material with PMMA and prismatic diffuser and construction as per IS : 10322 with driver as per the requirement with Driver efficiency >85%, Operating voltage AC 140-270 Volt, frequency 50/60 hz, Operating temp range -5 °C to 40 °C, internal surge protection of 2.5 KV with Short & Open circuit protection ,THD < 10% , P. F. ≥ 0.95 , IP20, CRI ≥ 80 , UGR (Unified Glare Rating) ≤ 19 Flicker free (flicker should be below 5 %), life time (LED, Driver & electrical circuitry), of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends, as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM (Standard Deviation Color Matching) <3, Maximum power consumption should not more than the specified rating and Fixture shall be to relevant BIS standard. Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. Complete in all respect with Minimum 5 year OEM warranty. System lumen efficacy $\geq 120 < 135$ lm/Watt output. LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C) Powder coated die cast /Extruded aluminium Body including trim., LED Batten Emergency (Inverter) luminaire, 1100 mm (nominal size), with a minimum system lumen output of 2000 lumen and a minimum system luminous efficacy of 100 lm/W, with built-in Li-ion rechargeable battery, suitable for operation on a 140-270V, 1 Φ , 50Hz AC supply system, complete with all accessories, electronic driver, diffuser etc., as required., Utility knife Tapaia UK-3, Spare Blade UB-10 for utility knife UK-3 Taparia, Flexible connection pipe 450mm Long, metal braided Hoses with steel /Brass Nuts & Rubber Washers suitable Geysers., Measuring Tape, Length of the Tape is 30 M. The width of the Blade is 13mm, Casing Capping clip, PVC Nail Clip 20 mm (Double Nail), Aluminium Paint ., Red Oxide Metal Primer, Paint Thinner (General Purpose), Paint Brush 2", Paint Brush 3", Wooden Screw 35 x 8 mm, Wooden Screw 50 x 8 mm, Dry wall /Gypsum Screw 3/4", Dry wall /Gypsum Screw 1", Dry wall/ Gypsum Screw 1½", 10 Amp, 12 way, PVC Strip Connector., 15 Amp, 12 way, PVC Strip Connector., Iron drill bit Set having 25 Pcs (PRO Metal HSS-G Twist Drill Bit Set 2607019446 of Bosch make, Self-supported FRP Platform Step Ladder with the following specifications: • Fully extended height: 10 feet • Minimum platform size: 300 mm (Length) x 250 mm (Width) • Anti-

बिड विवरण / Bid Details	skid rubber feet for stability • Weather-resistant construction suitable for outdoor use • Safety locking mechanism for secure operation • Anti-skid steps for user safety • Maximum load capacity: 140 kg • Warranty: 1 year, Installation Multifunction Testers with following features. 1. Capable of continuity testing, polarity testing, insulation resistance testing, and loop impedance testing of electrical wiring of residential and commercial buildings 2. voltage measurement between L-N, L-PE, and N-PE using the mains cord. 3. AC Voltage measurement upto 500V. 4. Measuring RCD trip current and trip time in parallel (RCD type AC and A) 5. Measuring PEFC or PSC and loop impedance in parallel and displays them together on the dual display. 6. Detects raised earth voltages > 50 V with Earth Volt Touchpad, indicating potential dangerous situations, 400 Amp 04 Pole Power contactor - conforms to IS/IEC 60947-4-1 & IEC 60947-4--1, Having frame size Fr-5 model MCX-43 suitable upto 250 KVA DG Set, Having Aux Contacts 2 NO + 2 NC, 16 Sq mm Aluminium Flat thimble (Tube Terminals), 25 Sq mm Aluminium Flat thimble (Tube Terminals), 50 Sq mm Aluminium Flat thimble (Tube Terminals), 70 Sq mm Aluminium Flat thimble (Tube Terminals), 95 Sq mm Aluminium Flat thimble (Tube Terminals), 120 sq mm Aluminium Flat thimble (Tube Terminals), 150 sq mm Aluminium Flat thimble (Tube Terminals), 185 sq mm Aluminium Flat thimble (Tube Terminals), 240 sq mm Aluminium Flat thimble (Tube Terminals), 300 sq mm Aluminium Flat thimble (Tube Terminals), 400 sq mm Aluminium Flat thimble (Tube Terminals), 16 Sq mm Aluminium Ferrule (In line connector), 25 Sq mm Aluminium Ferrule (In line connector), 35 Sq mm Aluminium Ferrule (In line connector), 50 Sq mm Aluminium Ferrule (In line connector), 70 Sq mm Aluminium Ferrule (In line connector), 70 watt Flood Light, powder coated pressure die cast aluminium body with built in or separate driver as per the requirement with Driver efficiency >85%, Input voltage: 140-270 Volt AC, frequency 50/60 hz, Operating temp range -5 °C to 50 °C, internal surge protection of 5 KV L,N,E as per IEC 61000-4-5, Driver efficiency >85%, THD< 10% as per IEC 61000-3-2 , P. F.≥0.95, IP-66, IK-10, CRI ≥70 , under voltage and over voltage protection, EMI-EMC as per CISPR-15, lenses for beam angle 30 deg-120deg as per the application and the project requirement, suitable tilt able fitting, life time (LED, Driver & electrical circuitary) of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM (Standard Deviation Color Matching) <5, Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard with Minimum 5 year OEM warranty. System lumen efficacy ≥120 and <135 lm/Watt output . LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted.. Shape size and CCT shall be as approved by Engineer-in- Charge as per requirement. (Thermal anagement: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C)., 150 watt Flood Light, powder coated pressure die cast aluminium body with built in or separate driver as per the requirement with Driver efficiency >85%, Input voltage: 140-270 Volt AC, frequency 50/60 hz, Operating temp range -5 °C to 50 °C, internal surge protection of 5 KV L,N,E as per IEC 61000-4-5, Driver efficiency >85%, THD< 10% as per IEC 61000-3-2 , P. F.≥0.95, IP-66, IK-10, CRI ≥70 , under voltage and over
<p>GeMARPTS में खोजी गई स्ट्रिंग्स / Searched Strings used in GeMARPTS</p>	

बिड विवरण / Bid Details

voltage protection, EMI-EMC as per CISPR-15, lenses for beam angle 30 deg-120deg as per the application and the project requirement, suitable tilt able fitting, life time (LED, Driver & electrical circuitary) of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM (Standard Deviation Color Matching) <5, Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard with Minimum 5 year OEM warranty. System lumen efficacy ≥ 120 and <135 lm/Watt output . LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted.. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal anagement: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C)., 45 watt Street light LED fixture powder coated pressure die cast aluminium body with driver as per the requirement with Driver efficiency >85%, Input voltage: 140-270 Volt AC, frequency 50/60 hz, Operating temp range -5 °C to 50 °C, internal surge protection of 5 KV L,N,E as per IEC 61000-4-5, Driver efficiency >85%, THD < 10% as per IEC 61000- 3-2 , P. F. ≥ 0.95 , IP-66, IK-10, CRI ≥ 70 , under voltage and over voltage protection, EMI-EMC As per CISPR 15 , lenses for beam angle as per IESNA type I/II/III as per the width of the road and the project requirement., suitable to fit in up to 65mm dia pipe, life time (LED,Driver & electrical circuitary) of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM(Standard Deviation Color Matching) <5, Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard with Minimum 5 year OEM warranty. System lumen efficacy ≥ 120 <135 lm/Watt output . LM79 & LM80 and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C)., 72 watt Street light LED fixture powder coated pressure die cast aluminium body with driver as per the requirement with Driver efficiency >85%, Input voltage: 140-270 Volt AC, frequency 50/60 hz, Operating temp range -5 °C to 50 °C, internal surge protection of 5 KV L,N,E as per IEC 61000-4-5, Driver efficiency >85%, THD < 10% as per IEC 61000- 3-2 , P. F. ≥ 0.95 , IP-66, IK-10, CRI ≥ 70 , under voltage and over voltage protection, EMI-EMC As per CISPR 15 , lenses for beam angle as per IESNA type I/II/III as per the width of the road and the project requirement., suitable to fit in up to 65mm dia pipe, life time (LED,Driver & electrical circuitary) of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM(Standard Deviation Color Matching) <5, Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard with Minimum 5 year OEM warranty. System lumen efficacy ≥ 120 <135 lm/Watt output . LM79 & LM80 and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction

बिड विवरण / Bid Details	temperature shall not rise above 90°C)., 90 watt Street light LED fixture powder coated pressure die cast aluminium
	<p>body with driver as per the requirement with Driver efficiency >85%, Input voltage: 140-270 Volt AC, frequency 50/60 hz, Operating temp range -5 °C to 50 °C, internal surge protection of 5 KV L,N,E as per IEC 61000-4-5, Driver efficiency >85%, THD < 10% as per IEC 61000- 3-2 , P. F.≥0.95, IP-66, IK-10, CRI ≥70, under voltage and over voltage protection, EMI-EMC As per CISPR 15 , lenses for beam angle as per IESNA type I/II/III as per the width of the road and the project requirement., suitable to fit in up to 65mm dia pipe, life time (LED,Driver & electrical circuitary) of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM(Standard Deviation Color Matching) <5, Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard with Minimum 5 year OEM warranty. System lumen efficacy ≥120 <135 lm/Watt output . LM79 & LM80 and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C)., 150 watt Street light LED fixture powder coated pressure die cast aluminium body with driver as per the requirement with Driver efficiency >85%, Input voltage: 140-270 Volt AC, frequency 50/60 hz, Operating temp range -5 °C to 50 °C, internal surge protection of 5 KV L,N,E as per IEC 61000-4-5, Driver efficiency >85%, THD < 10% as per IEC 61000- 3-2 , P. F.≥0.95, IP-66, IK-10, CRI ≥70, under voltage and over voltage protection, EMI-EMC As per CISPR 15 , lenses for beam angle as per IESNA type I/II/III as per the width of the road and the project requirement., suitable to fit in up to 65mm dia pipe, life time (LED,Driver & electrical circuitary) of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM(Standard Deviation Color Matching) <5, Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard with Minimum 5 year OEM warranty. System lumen efficacy ≥120 <135 lm/Watt output . LM79 & LM80 and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C)., 10 to 11 Watt, 0.6 Metre (nominal size) LED Bollard Light fitting complete with LED module, electronic driver with minimum Surge Voltage protection 3 kV, diffuser, and all other accessories, minimum system luminous efficacy of 80 lm/W and Average life L70B50: 50000 hours, IP65, IK07, Operating voltage range: 140 V - 270 V, the bollard housing should be made up of metallic pipe duly powder coated with the mounting flange at the bottom. The seller shall provide five years manufacturers' warranty for complete luminaire., 25-watt LED-based post-top luminaire, IP 65, with Die-cast aluminium spigot housing, complete with diffuser, LED module, electronic driver with surge protection of ≥10KV, PF >0.9, and all other accessories, having minimum system luminous efficacy of 95 lm/W, operating voltage range: 140 V - 270 V, and average luminaire life L70B50: 50000 hours.</p>

बिड विवरण / Bid Details

The seller shall provide five years manufacturers' warranty for complete luminaire., 10 Watt to 12 Watt Spike LED light with aluminium housing, IP66 having tiltable feature to throw light in the desired direction., Straight through cable jointing kit with heat shrinkable kit with ferrules for 1.1 KV grade cable. Size 2 X 16 sq. mm sq. mm 1.1 KV grade cable., Straight through cable jointing kit with heat shrinkable kit with ferrules for 1.1 KV grade cable. Size 2 X 25 sq. mm sq. mm 1.1 KV grade cable., Straight through cable jointing kit with heat shrinkable kit with ferrules for 1.1 KV grade cable. Size 3½ X 35 sq. mm sq. mm 1.1 KV grade cable., Straight through cable jointing kit with heat shrinkable kit with ferrules for 1.1 KV grade cable. Size 3½ X 300 sq. mm 1.1 KV grade cable., Cable Junction Boxes, IP 66 weather proof, size 205 mm x 255 mm x 112 mm, with terminals suitable for 16 sq mm cable., 4 Inch Cutting Wheel for Metal suitable for 4" angle grinder., 1.5 Volt Alkaline non-rechargeable, type battery, size- AAA., 1.5 Volt Alkaline non-rechargeable, type battery, size- AA., 9 Volts Alkaline non-rechargeable Battery, 23A, 12V Alkaline Battery., LED Rope Light, (10 watt/metre or 120 LED per metre) in various colors, IP65 rating, with adopter ., Supplying of Adapter for LED Rope Light., LED Rope Light, (6 W/ Mtr), IP65, Tri-Color. 18 Meter., Supplying Pidilite WD 40 mechanical contact cleaner in 500 ml can with Straw Spray., 2 x 16 sq mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade , confirming to IS : 7098 (Part-1) 1988 with upto Date Amendments., 2 x 25 sq mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade , confirming to IS : 7098 (Part-1) 1988 with upto Date Amendments, 3.5 x 35 sq mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade , confirming to IS : 7098 (Part-1) 1988 with upto Date Amendments, 3.5 x 120 sq mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade , confirming to IS : 7098 (Part-1) 1988 with upto Date Amendments., 3.5 x 400 sq mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade , confirming to IS : 7098 (Part-1) 1988 with upto Date Amendments, Socket tester to verify that the wall socket is correctly wired and to check for common faults, such as a missing earth connection, with the following features: LCD display Data hold function Three-hole socket line sequence detection Phase voltage (L-N) measurement Leakage voltage (N-E) measurement RCD (or GFCI) test Socket sequence test Automatic shutdown function Detection of wiring errors Trip time test, M-Seal - Regular epoxy compound., Pu Foam Insulation Sealant 750 ml, Distilled Water, 5 Liters, Weatherproof (IP66) wire connector with plug and socket suitable for 4 sq mm copper cable., Digital Earth Resistance Tester (KUSAM MECO KM-2030 or equivalent specification, PVC Weatherproof, IP65, 8 module MCB DB with DIN rail., Wall-Mounted Voltage Stabilizer, Suitable for 1.5 Ton Split Air Conditioner. The stabilizer shall be wall-mounted type and equipped with the following features: High and Low Voltage Cut-off Protection Thermal Overload Protection Time Delay Relay (TDR) Working Voltage Range: 150 - 285 Volts. Warranty: Minimum 3 years., Wall-Mounted Voltage Stabilizer, Suitable for 2 Ton Split Air Conditioner. The stabilizer shall be wall-mounted type and equipped with the following features: High and Low Voltage Cut-off Protection Thermal Overload Protection Time Delay Relay (TDR) Working Voltage Range: 150 - 285 Volts. Warranty:

विड विवरण / Bid Details	Minimum 3 years., Blue Plastic Crate, 4 Litre Capacity, Size: 300 x 200 x 100 mm, suitable for material storage., PVC
	<p>Weatherproof Switch Box (IP66 Rated) Weatherproof enclosure (IP66), suitable for outdoor use. complete with: One Single Pole Switch, and One 3-pin 16 A Socket Outlet, 240V., (6 / 16) A Power adaptor with in-built RCD 30 ma, Robustt Caution Tape "3 Inches x 130 Mtr" (Pack of 1) White & Red PVC Material, Barrication tape/Danger/Men at work Barricading Tape, Warning Tape Weather Resistant, Polypropylene Floor Standing Caution Sign Board Type: "Caution Men At Work" message, two-sided floor sign board Size (Nominal) : 62 cm (H) x 30 cm (W) Design: Foldable, floor-standing, double-sided visibility, Stainless Steel Clip for fixing LED batten as per sample provided by department., Waterproof Paint Marker, Suitable for marking on: Metal, plastic, glass, fabric, and similar surfaces. Bullet shaped Acrylic Nib, Line Width Approx. 2.2mm - 2.8 mm, Ink Colour: As per requirement, to be approved by the Engineer-in-Charge. ,, 15A insulated test lead cable with dual-ended insulated crocodile clips, suitable for electrical testing. Set of 5 Pc. (, Plastic Step Stool, Nominal Dimensions: Width - 57 cm, Depth - 54 cm, Height - 60 cm, 30W 220V Round Corded Soldering Iron with LED Worklight . 6 Months Warranty., Solder Paste Flux Pack -50 gm, Lead-Free Soldering Wire, 0.8 mm diameter, suitable for electronic and electrical soldering and component repair. 20-gram pack., Cleaning Cloth Towels, Material: 100% cotton, Suitable for dirt and surface cleaning in general maintenance, Size: 35 cm x 35 cm (nominal), Soft, absorbent, reusable, and washable (, Microfiber Multi-Purpose Cleaning Wipe, suitable for both dry and wet cleaning of surfaces such as glass, plastic, and metal; nominal size 29.2 cm x 29.2 cm, Contactless Surface Temperature Detector. Suitable for non-contact measurement of surface temperature. Measurement Range: -30 °C to +500 °C (Surface Temperature) Operating Temperature: -5 °C to +50 °C, PVC Plastic Pipe Cutter, Cutting Capacity: Up to 42 mm (maximum),, HSS Bi-metal Holesaw Set, 20-64 mm diameter; hole saw sizes: 20, 25, 32, 38, 51, and 64 mm, Plastic Tool Box with Organizer, Height 150 mm, width 190 mm, length 335 mm, High carbon steel Shovel with Wooden Handle., Hoe (Powrahs) (Make TATA HOE031 - TP 5 Gold or another make of similar specification, as approved by the Engineer-in-Charge), High Tempered Iron Pickaxe (Gaiti) with Wooden Handle. Weight (Approx.) : 1.1 kg, Aluminium /Aluminium Alloy Self-Supporting Type Tower Ladder (Extendable) Fabricated from aluminium sections of size 66 mm (2 5/8") x 31 mm (1 1/4") x 3 mm (1/8") thick (approx.). Steps are made from 25 mm (1") diameter fluted aluminium pipe, spaced at 300 mm (12") intervals. The ladder is equipped with aluminium casted pulley, sisal/nylon rope, and self-locking pawls to ensure secure and adjustable height operation. Base Support: • Two (2) solid rubber wheels on one side for easy mobility. • Two (2) rubber shoes on the opposite side for ground grip and stability during use. • Includes 50 x 50 x 5 mm MS angle brackets for added sturdiness during operation. Additional Features: Complete with handle, side railing, and a top safety ring to ensure user safety at elevated heights. Dimensions: • Closed Height: 20 ft • Extended Height: 36 ft</p>
	<p>Searched String: PVC Pendant Holder, PVC Insulated Unsheathed Cable with Flexible Conductor (V2) Marked To IS 694, Soldering Clamp Holder, ID Card Holder (V2), Tooth brush Holder, PVC Insulated Copper Cable Single Core and Multi Core Circular Sheathed with Rigid Conductor (V2) ISI Marked To IS 694, Plane Mirror Strip Holder, PVC Insulated Copper Cable Single Core and Multi Core Circular Sheathed with Flexible</p>

बिड विवरण / Bid Details

Conductor (V2) ISI Marked To IS 694, Business Card Holder (V2), PVC Insulated Copper Cord Single Core and Multi Core Circular Sheathed with Flexible Conductor (V2) ISI Marked To IS 694

Searched String: One way. Bed switch, 240 v, 50 Hz
D.C. Earth Fault Locator, Exercise Bike

Searched String: Single pole 10 amps, two way switch, ISI marked. Modular type
Modular Piano Type Domestic Electrical Switches ISI Marked To IS 3854, Non Modular Piano Type Domestic Electrical Switches ISI Marked To IS 3854

Searched String: Modular Bell Push Switch. Modular type
modular electrical enclosure switch board boxes for modular type accessories, Modular Piano Type Domestic Electrical Switches ISI Marked To IS 3854, Mobile Storage Compactors, Online Ups Modular Type, Non Modular Piano Type Domestic Electrical Switches ISI Marked To IS 3854, Modular Piano Type Domestic Electrical Sockets ISI Marked To IS 1293, Non Modular Piano Type Domestic Electrical Sockets ISI Marked To IS 1293, Modular Piano Type Domestic Fan Regulator Conforming To IS 11037, Non Modular Piano Type Domestic Fan Regulator Conforming To IS 11037, Director-Class Storage Area Network (SAN) Switch

Searched String: Modular blanking plate
Blanking cap, Modular Table / Meeting Table / Centre Table (V2), Modular Toilet, Modular Control Desk, Modular Metal Drawer File Cabinet Pedestal, Modular Cold Rooms, Multipara Monitor - Low End, Online Ups Modular Type, Wooden Shelf / Case / Rack / Credenza / Modular Storage (V2), Modular Work Stations (V3)

Searched String: Single pole 25 amps, one way modular switch, ISI marked.
Category not available on GeM for the text string uploaded by the buyer

Searched String: 2 module, Modular base & cover plate
MCCB with Thermal Magnetic / Microprocessor Based Trip Unit, modular electrical enclosure switch board boxes for modular type accessories, Modular Work Stations (V3), Multipara Monitor - Low End, Wooden Shelf / Case / Rack / Credenza / Modular Storage (V2), Locking Compression Plates (V2)

Searched String: 3 module, Modular base & cover plate
Locking Compression Plates (V2), modular electrical enclosure switch board boxes for modular type accessories, MCCB with Thermal Magnetic / Microprocessor Based Trip Unit, Welding Electrode - Covered Arc Welding Electrode - Rutile Type (BEML), Modular Work Stations (V3)

Searched String: 4 module, Modular base & cover plate
modular electrical enclosure switch board boxes for modular type accessories, Welding Electrode - Covered Arc Welding Electrode - Rutile Type (BEML), Modular Work Stations (V3),

विड विवरण / Bid Details Locking Compression Plates (V2)

Searched String: 6 module, Modular base & cover plate

modular electrical enclosure switch board boxes for modular type accessories, Modular Work Stations (V3)

Searched String: 12 module, Modular base & cover plate

modular electrical enclosure switch board boxes for modular type accessories, 7 Watt White-LED Based Solar Street Lighting System As Per MNRE Specification, Modular Work Stations (V3), Solar Lamps (Solar Based Home Systems - Solar Power Packs - AC Models)

Searched String: Flame - Retardant, PVC Electrical insulation Tapes 6 mtr X 1.8 cm long

Category not available on GeM for the text string uploaded by the buyer

Searched String: PVC gitti / PVC rawal plug /PVC fastener 38/40mm long/PVC fastener 38/40mm long

PVC Insulated Copper Cable Single Core and Multi Core Circular Sheathed with Rigid Conductor (V2) ISI Marked To IS 694, PVC Insulated Copper Cord Single Core and Multi Core Circular Sheathed with Flexible Conductor (V2) ISI Marked To IS 694, PVC Sheet (V2), PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1), Flat Cable, Copper Conductor with PVC Insulation and Sheathed ISI Marked To IS 694, PVC Insulated Unsheathed Cable with Rigid Conductor (V2) ISI Marked To IS 694, PVC Single Core and Multi Core Circular Sheathed Aluminium Cable with Rigid Conductor (V2) as per IS 694, Vertical Blinds (V2), Flexible Drain Hoses for Wash Basins/ Sinks

Searched String: 3 mm thick phenolic laminated sheet.

Phenolic Laminated Sheets As per IS 2036, traffic signs - bilinker light, PP Plastic Woven Non - Laminated Bags (for Seed Packaging) (V2), Polymethyl Methacrylate (PMMA) (Acrylic) Sheets (V2) as per IS 14753 (Latest), Computer Paper (V3) Conforming to IS 12766 (In Packet), Corrugated Boxes, Decorative Laminate Sheet, Gasket Sheet-IS:11149, Linoleum Sheet & Tiles (V2) Conforming to IS 653, MS Sheet as per IS 1079

Searched String: 1.5 Sq. mm. FRLS / HFFR single core, multi strand copper conductor, PVC insulated cable suitable upto 1100 volts

PVC Insulated Copper Cable Single Core and Multi Core Circular Sheathed with Rigid Conductor (V2) ISI Marked To IS 694, PVC Insulated Copper Cable Single Core and Multi Core Circular Sheathed with Flexible Conductor (V2) ISI Marked To IS 694, PVC Insulated Copper Cord Single Core and Multi Core Circular Sheathed with Flexible Conductor (V2) ISI Marked To IS 694, PVC Single Core and Multi Core Circular Sheathed Aluminium Cable with Rigid Conductor (V2) as per IS 694

Searched String: 4 Sq. mm. FRLS / HFFR single core, multi strand copper conductor, PVC insulated cable suitable upto 1100 volts

PVC Insulated Copper Cable Single Core and Multi Core

बिड विवरण / Bid Details

Circular Sheathed with Rigid Conductor (V2) ISI Marked To IS 694, PVC Insulated Copper Cable Single Core and Multi Core

Circular Sheathed with Flexible Conductor (V2) ISI Marked To IS 694, PVC Insulated Copper Cord Single Core and Multi Core Circular Sheathed with Flexible Conductor (V2) ISI Marked To IS 694, PVC Single Core and Multi Core Circular Sheathed Aluminium Cable with Rigid Conductor (V2) as per IS 694

Searched String: 6.0 Sq. mm. FRLS/HFFR single core, multi strand copper conductor, PVC insulated cable suitable upto 1100 volts

PVC Insulated Copper Cable Single Core and Multi Core Circular Sheathed with Flexible Conductor (V2) ISI Marked To IS 694, PVC Insulated Copper Cable Single Core and Multi Core Circular Sheathed with Rigid Conductor (V2) ISI Marked To IS 694, Flat Cable, Copper Conductor with PVC Insulation and Sheathed ISI Marked To IS 694, PVC Insulated Copper Cord Single Core and Multi Core Circular Sheathed with Flexible Conductor (V2) ISI Marked To IS 694, PVC Single Core and Multi Core Circular Sheathed Aluminium Cable with Rigid Conductor (V2) as per IS 694, PVC Insulated Unsheathed Cable with Rigid Conductor (V2) ISI Marked To IS 694

Searched String: Modular MCB single pole 25 Amp "C" curve, 3 kA breaking capacity.

Category not available on GeM for the text string uploaded by the buyer

Searched String: Pin Anchor Fastener 6 x 50

modular electrical enclosure switch board boxes for modular type accessories, Cotton Cloth Bag for Seed Packing - Capacity From 0.75 Kg to 12 Kg - National Seeds Corporation Limited, Non Modular Piano Type Domestic Electrical Sockets ISI Marked To IS 1293, Polyurethane Tube (V2), Modular Piano Type Domestic Electrical Sockets ISI Marked To IS 1293

Searched String: Pin Anchor Fastener 8 x 50

Work Benches, modular electrical enclosure switch board boxes for modular type accessories, Polyurethane Tube (V2)

Searched String: Pin Anchor Fastener 8 x 75

modular electrical enclosure switch board boxes for modular type accessories, Equipment Camouflage Nets (Jute) as per Defence Specification

Searched String: Pin Anchor Fastener 10 x 100

Mechanically Woven, Double - Twisted, Hexagonal Wire Mesh Gabions, Revet Mattresses and Rock Fall Netting as per IS 16014, modular electrical enclosure switch board boxes for modular type accessories, Modular Toilet, Metallurgical Microscope

Searched String: Ring Hook Fastener M-8

Conveyer Belt Fastening Hook, water baths, Fastener for Consumer Goods - Synthetic Hook and Loop Tape as per IS 8156, General Purpose Hand Gloves (V2), File/Folder (V3), Stainless Steel Threaded Fasteners as per IS 1367(Part 14),

बिड विवरण / Bid Details

Environmental Chamber, Mechanically Woven, Double - Twisted, Hexagonal Wire Mesh Gabions, Revet Mattresses and Rock Fall Netting as per IS 16014, Shaker Incubator, SEWAGE TREATMENT PLANT

Searched String: Ring Hook Fastener M-10

Conveyer Belt Fastening Hook, water baths, Fastener for Consumer Goods - Synthetic Hook and Loop Tape as per IS 8156, Humidity Chamber, Mechanically Woven, Double - Twisted, Hexagonal Wire Mesh Gabions, Revet Mattresses and Rock Fall Netting as per IS 16014, Environmental Chamber, Stainless Steel Threaded Fasteners as per IS 1367(Part 14), Plaster of Paris Bandage Conforming to IS 4738, Galvanized Steel Chain Link Fence Fabric (V2) conforming to IS 2721, Double sided tape

Searched String: Wedge Anchor Fastener 8 mm x 75 mm

modular electrical enclosure switch board boxes for modular type accessories, Wooden Lab Stools, Portable Toilet, Work Benches, Sterile Hypodermic Needles for Single use (V2), Mechanically Woven, Double - Twisted, Hexagonal Wire Mesh Gabions, Revet Mattresses and Rock Fall Netting as per IS 16014, Equipment Camouflage Nets (Jute) as per Defence Specification, Polyurethane Tube (V2), Modular Toilet, Scalp Vein (Winged Needle) Infusion Set Conforming to IS 16097

Searched String: 3 mm thick PVC/ phenolic laminated round sheet cover minimum 170 mm dia for fan box.

Phenolic Laminated Sheets As per IS 2036

Searched String: 3 mm thick PVC / phenolic laminated round sheet cover 100 mm dia.

Phenolic Laminated Sheets As per IS 2036

Searched String: 3 module , PVC Surface Modular box

PVC gitti, modular electrical enclosure switch board boxes for modular type accessories

Searched String: 6 module , PVC Surface Modular box

PVC gitti, modular electrical enclosure switch board boxes for modular type accessories

Searched String: BEE 5 star rating, 25 litres capacity water storage heater, with protection against over heating, Multifunction Safety Valve and external adjustable thermostat, with 16 A, 240 V, plug top with in-built 30 mA RCD and 02 nos flexible connection pipe suitable for working with 230V AC, 50 Hz, 1 Phase supply etc as required. (with 7 year warranty on inner tank, 3 year warranty on heating element, 2 year comprehensive Warranty)

Category not available on GeM for the text string uploaded by the buyer

Searched String: 1200 mm sweep, BEE 5 star rated, ceiling fan with Brush Less Direct Current (BLDC) Motor, class of insulation B, 3 nos. blades, down rod upto 30 cm long , 2 nos. canopies, shackle kit, safety rope, copper winding, Power Factor not less than 0.9, Service Value

बिड विवरण / Bid Details

(CMM/W) minimum 8.00, Air delivery minimum 215 CMM, 350 RPM (tolerance as per IS 374-2019), THD less than 10%, without remote and compatible with existing step electronic regulator unit for speed control and all remaining accessories including safety pin, nut bolts, washers, temperature rise 75 degree C (max.), insulation resistance more than 2 mega ohm, suitable for 230 V, 50 Hz, single phase AC Supply. The firm has to submit a type test report of the ceiling fan from a NABL accredited lab before commencement of supply. (BLDC Ceiling fan with minimum 2 years Warranty)

Category not available on GeM for the text string uploaded by the buyer

Searched String: Supply of 400 MM, Single phase wall mounting fan

Bathroom Water Shower (V2), Corrugated Boxes

Searched String: Fresh air fan with louver shutter 250 mm sweep.

Category not available on GeM for the text string uploaded by the buyer

Searched String: 230 mm sweep, 1400 RPM , single phase, metallic exhaust fan Conforming to IS:2312 -1967.

Category not available on GeM for the text string uploaded by the buyer

Searched String: Metallic louvred shutter suitable for 300 mm sizes exhaust fan.

Electric Pedestal Type Fan and Regulator as per IS 1169

Searched String: Metallic louvred shutter suitable for 380 mm sizes exhaust fan.

Category not available on GeM for the text string uploaded by the buyer

Searched String: 18- 22 watt LED surface mounted Batten light of following body material and construction as per IS : 10322 with driver (Replaceable) as per the requirement with Driver efficiency >85%, Operating voltage AC 140-270 Volt, frequency 50/60 hz, Operating temp range -5 °C to 40 °C, internal surge protection of 2.5 KV with Short & Open circuit protection ,THD < 10% , P. F. ≥ 0.95, IP20, CRI ≥ 80 , Flicker free (flicker should be below 5 %), life time (LED, Driver & electrical circuitry), of minimum 50000 Burning Hours with , 70% of initial Lumen maintained till life ends, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM(Standard Deviation Color Matching) <3, Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard. Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. with Minimum 5 year OEM warranty. System lumen efficacy ≥120 <135 lm/Watt output LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C). Powder coated die cast / Extruded aluminium Body (Thickness ≥ 1.20 mm)

बिड विवरण / Bid Details

Category not available on GeM for the text string uploaded by the buyer

Searched String: 40 watt LED surface mounted Batten light of following body material and construction as per IS : 10322 with driver (Replaceable) as per the requirement with Driver efficiency >85%, Operating voltage AC 140-270 Volt, frequency 50/60 hz, Operating temp range -5 °C to 40 °C, internal surge protection of 2.5 KV with Short & Open circuit protection ,THD < 10% , P. F. ≥ 0.95, IP20, CRI ≥ 80 , Flicker free (flicker should be below 5 %), life time (LED, Driver & electrical circuitry), of minimum 50000 Burning Hours with , 70% of initial Lumen maintained till life ends, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM(Standard Deviation Color Matching) <3, Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard. Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. with Minimum 5 year OEM warranty. System lumen efficacy ≥120 <135 lm/Watt output LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C). Powder coated die cast / Extruded aluminium Body (Thickness ≥ 1.20 mm)

Category not available on GeM for the text string uploaded by the buyer

Searched String: 5-7 watt LED Recessed/surface Down lighter (Round / square/ Rectangular) SMD type of following body material with PMMA and prismatic diffuser and construction as per IS : 10322 with driver as per the requirement with Driver efficiency >85%, Operating voltage AC 140-270 Volt, frequency 50/60 hz, Operating temp range -5 °C to 40 °C, internal surge protection of 2.5 KV with Short & Open circuit protection ,THD < 10% , P. F.≥0.95, IP20, CRI ≥80 , UGR (Unified Glare Rating) ≤ 19 Flicker free (flicker should be below 5 %), life time (LED, Driver & electrical circuitry), of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends, as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM (Standard Deviation Color Matching) <3, Maximum power consumption should not more than the specified rating and Fixture shall be to relevant BIS standard. Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. Complete in all respect with Minimum 5 year OEM warranty. System lumen efficacy ≥120 <135 lm/Watt output. LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C) Powder coated die cast /Extruded aluminium Body including trim.

Category not available on GeM for the text string uploaded by the buyer

Searched String: 12 -15 watt LED Recessed/surface Down lighter (Round / square/ Rectangular) SMD type of following body material with PMMA and prismatic diffuser and

बिड विवरण / Bid Details

construction as per IS : 10322 with driver as per the requirement with Driver efficiency >85%, Operating voltage AC 140-270 Volt, frequency 50/60 hz, Operating temp range -5 °C to 40 °C, internal surge protection of 2.5 KV with Short & Open circuit protection ,THD < 10% , P. F.≥0.95, IP20, CRI ≥80 , UGR (Unified Glare Rating) ≤ 19 Flicker free (flicker should be below 5 %), life time (LED, Driver & electrical circuitry), of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends, as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM (Standard Deviation Color Matching) <3, Maximum power consumption should not more than the specified rating and Fixture shall be to relevant BIS standard. Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. Complete in all respect with Minimum 5 year OEM warranty. System lumen efficacy ≥120 <135 lm/Watt output. LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C) Powder coated die cast /Extruded aluminium Body including trim.

Category not available on GeM for the text string uploaded by the buyer

Searched String: 18 watt LED Recessed/surface Down lighter (Round / square/ Rectangular) SMD type of following body material with PMMA and prismatic diffuser and construction as per IS : 10322 with driver as per the requirement with Driver efficiency >85%, Operating voltage AC 140-270 Volt, frequency 50/60 hz, Operating temp range -5 °C to 40 °C, internal surge protection of 2.5 KV with Short & Open circuit protection ,THD < 10% , P. F.≥0.95, IP20, CRI ≥80 , UGR (Unified Glare Rating) ≤ 19 Flicker free (flicker should be below 5 %), life time (LED, Driver & electrical circuitry), of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends, as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM (Standard Deviation Color Matching) <3, Maximum power consumption should not more than the specified rating and Fixture shall be to relevant BIS standard. Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. Complete in all respect with Minimum 5 year OEM warranty. System lumen efficacy ≥120 <135 lm/Watt output. LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C) Powder coated die cast /Extruded aluminium Body including trim.

Category not available on GeM for the text string uploaded by the buyer

Searched String: LED Batten Emergency (Inverter) luminaire, 1100 mm (nominal size), with a minimum system lumen output of 2000 lumen and a minimum system luminous efficacy of 100 lm/W, with built-in Li-ion rechargeable battery, suitable for operation on a 140-270V, 1Φ, 50Hz AC supply system, complete with all accessories,

बिड विवरण/Bid Details

electronic driver, diffuser etc., as required.

Category not available on GeM for the text string uploaded by the buyer

Searched String: Utility knife Tapaia UK-3

Category not available on GeM for the text string uploaded by the buyer

Searched String: Spare Blade UB-10 for utility knife UK-3 Taparia

Category not available on GeM for the text string uploaded by the buyer

Searched String: Flexible connection pipe 450mm Long, metal braided Hoses with steel /Brass Nuts & Rubber Washers suitable Geysers.

Category not available on GeM for the text string uploaded by the buyer

Searched String: Measuring Tape, Length of the Tape is 30 M. The width of the Blade is 13mm

Pedestrian-Controlled Lawn Mower

Searched String: Casing Capping clip

Cable Nail Clip (V2), Molded Case Circuit Breakers (MCCB) as per IS / IEC 60947, Circlips - IS 3075, Ligation Clips, Open / Endoscopic Clip Applicator (V2), Regular Casing Pipes (ONGC), Medical Caps Conforming to IS 17629, HX Casing Head (CMPDI), Wooden Shelf / Case / Rack / Credenza / Modular Storage (V2), NX Casing Head (CMPDI)

Searched String: PVC Nail Clip 20 mm (Double Nail)

Cable Nail Clip (V2), Nail Cutter, Theft Proof Rifle Racks, Double sided tape

Searched String: Aluminium Paint .

Heat Resistant Aluminium Paint - BHEL, XLPE Cable for Working Voltages up to and Including 1.1 KV as per IS 7098 (Part 1), Aluminium Paint, Heat Resistant as per IS 13183, Paint spray gun, Fabric Paint, Enamel, Synthetic, Exterior (A) Undercoating (B) Finishing (V4) Confirming to IS 2932, Electrical Insulating Paint, Fire Retardant paint, magnetic stirrers, Enamel paint remover

Searched String: Red Oxide Metal Primer

Metal Oxide Gap-less (ZnO) Type Surge Arrestor (BHEL), Ready Mixed Paint, Air Drying, Red Oxide Zinc Chrome, Priming (V2) as per IS 2074, Metal Oxide Surge Arresters Without Gaps For A.C. Systems (V2) Conforming to IS 15086 (Part 4), Ready Mixed Paint, Air Drying, Red Oxide - Zinc Phosphate, Priming as per IS 12744, Enamel, Synthetic, Exterior (A) Undercoating (B) Finishing (V4) Confirming to IS 2932

Searched String: Paint Thinner (General Purpose)

Thinner for Synthetic Paint and Varnishes Conforming to IS 14314, Non Refrigerated Centrifuge for General Purpose and research, Thinner For Epoxy Paints (BHEL), Shovel Belcha as

बिड विवरण / Bid Details	per IS 274 (Part 1, Part 2 and Part 3), Ready Mixed Paint, Air Drying, for General Purpose (V2) Conforming to IS 168,
	<p>Electronic Weighing Scales, General purpose safety pins, Chair for General Purpose, General Purpose Battery Chargers, General Purpose Tool Kit</p> <p>Searched String: Paint Brush 2"</p> <p>Flat Brushes for Paints and Varnishes for Heavy Duty (V2) conforming to IS 384 (Part 1), Sofa (V3), cobweb brush, platform brush, scrubbing brush, XLPE Cable for Working Voltages up to and Including 1.1 KV as per IS 7098 (Part 1), Ready Mixed Paint, Brushing, Acid Resisting, Desk and Bench Set for Classroom/Training Area, Fabric Paint, Enamel, Synthetic, Exterior (A) Undercoating (B) Finishing (V4) Confirming to IS 2932</p> <p>Searched String: Paint Brush 3"</p> <p>Flat Brushes for Paints and Varnishes for Heavy Duty (V2) conforming to IS 384 (Part 1), High End Desktop Computer, cobweb brush, platform brush, Entry and Mid Level Desktop Computer, scrubbing brush, Sofa (V3), Ready Mixed Paint, Brushing, Acid Resisting, XLPE Cable for Working Voltages up to and Including 1.1 KV as per IS 7098 (Part 1), Fabric Paint</p> <p>Searched String: Wooden Screw 35 x 8 mm</p> <p>Wooden Lab Stools, Work Benches, Wooden Flooring (V3), Bone Screw (V2), Compostable Carry Bags, Locking Compression Plates (V2), Sterile Hypodermic Needles for Single use (V2), Mechanically Woven, Double - Twisted, Hexagonal Wire Mesh Gabions, Revet Mattresses and Rock Fall Netting as per IS 16014, Compostable Nursery Bags, Polyurethane Tube (V2)</p> <p>Searched String: Wooden Screw 50 x 8 mm</p> <p>modular electrical enclosure switch board boxes for modular type accessories, Wooden Flooring (V3), Wooden Lab Stools, Work Benches, Cast Iron Bench, Compostable Nursery Bags, Sterile Hypodermic Needles for Single use (V2), Mechanically Woven, Double - Twisted, Hexagonal Wire Mesh Gabions, Revet Mattresses and Rock Fall Netting as per IS 16014, Polyurethane Tube (V2), Equipment Camouflage Nets (Jute) as per Defence Specification</p> <p>Searched String: Dry wall /Gypsum Screw 3/4"</p> <p>Centrifugal/Screw Compressor with Dryer (NALCO), Wall Mounting Cabinet, Biological Indicators For Dry Heat Sterilization Processes Conforming to IS/ISO 11138 (Part 4), General Purpose Ball Valves conforming to IS 9890, Hand Dryer (V3), Bone Screw (V2), Laboratory Drying Oven, Reverse Osmosis based Point of Use Water Treatment System for Drinking Purposes (V3) as per IS 16240, Screw Compressor, Copper alloy Taps/Stop Valves (V2) Conforming to IS 8931</p> <p>Searched String: Dry wall /Gypsum Screw 1"</p> <p>Plain Gypsum Plaster Board ISI Marked to IS 2095 (Part 1), Laboratory Drying Oven, Centrifugal/Screw Compressor with Dryer (NALCO), Laboratory Glassware Bottles (Screw - Neck Bottles) as per IS 1388 (Part 1), Flat Brushes for Paints and Varnishes for Heavy Duty (V2) conforming to IS 384 (Part 1),</p>

बिड विवरण / Bid Details

Hand Dryer (V3), Wall Mounting Cabinet, Copper alloy Taps/Stop Valves (V2) Conforming to IS 8931, Cordless screw driver, Dry Block Heater

Searched String: Dry wall/ Gypsum Screw 1½"

Plain Gypsum Plaster Board ISI Marked to IS 2095 (Part 1), Laboratory Drying Oven, Centrifugal/Screw Compressor with Dryer (NALCO), General Purpose Ball Valves conforming to IS 9890, Laboratory Glassware Bottles (Screw - Neck Bottles) as per IS 1388 (Part 1), Flat Brushes for Paints and Varnishes for Heavy Duty (V2) conforming to IS 384 (Part 1), Gypsum Building Plaster - Excluding Premixed as per IS 2547, Hand Dryer (V3), Wall Mounting Cabinet, Copper alloy Taps/Stop Valves (V2) Conforming to IS 8931

Searched String: 10 Amp, 12 way, PVC Strip Connector.

shoes school pvc boys girls, Connector Pipes for Washbasins/ Sinks/ Geyser

Searched String: 15 Amp, 12 way, PVC Strip Connector.

Connector Pipes for Washbasins/ Sinks/ Geyser, Two Way Valve, PVC Insulated Copper Cable Single Core and Multi Core Circular Sheathed with Flexible Conductor (V2) ISI Marked To IS 694, Needle Free Connector with Extension Tube

Searched String: Iron drill bit Set having 25 Pcs (PRO Metal HSS-G Twist Drill Bit Set 2607019446 of Bosch make

Category not available on GeM for the text string uploaded by the buyer

Searched String: Self-supported FRP Platform Step Ladder with the following specifications: • Fully extended height: 10 feet • Minimum platform size: 300 mm (Length) × 250 mm (Width) • Anti-skid rubber feet for stability • Weather-resistant construction suitable for outdoor use • Safety locking mechanism for secure operation • Anti-skid steps for user safety • Maximum load capacity: 140 kg • Warranty: 1 year

Category not available on GeM for the text string uploaded by the buyer

Searched String: Installation Multifunction Testers with following features. 1. Capable of continuity testing, polarity testing, insulation resistance testing, and loop impedance testing of electrical wiring of residential and commercial buildings 2. voltage measurement between L-N, L-PE, and N-PE using the mains cord. 3. AC Voltage measurement upto 500V. 4. Measuring RCD trip current and trip time in parallel (RCD type AC and A) 5. Measuring PEFC or PSC and loop impedance in parallel and displays them together on the dual display. 6. Detects raised earth voltages > 50 V with Earth Volt Touchpad, indicating potential dangerous situations

Category not available on GeM for the text string uploaded by the buyer

Searched String: 400 Amp 04 Pole Power contactor - conforms to IS/IEC 60947-4-1 & IEC 60947-4--1, Having frame size Fr-5 model MCX-43 suitable upto 250 KVA DG Set, Having Aux Contacts 2 NO + 2 NC

बिड विवरण / Bid Details Category not available on GeM for the text string uploaded by the buyer

GeMARPTS में खोजा गया परिणाम / Searched Result generated in GeMARPTS

Searched String: 16 Sq mm Aluminium Flat thimble (Tube Terminals)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1), Flat Cable, Copper Conductor with PVC Insulation and Sheathed ISI Marked To IS 694, Terminal Ends for Aluminium Conductors of Insulated Cables (Compression Cable Lugs) Conforming To IS 8309

Searched String: 25 Sq mm Aluminium Flat thimble (Tube Terminals)

Flat Cable, Copper Conductor with PVC Insulation and Sheathed ISI Marked To IS 694, PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1), PVC Single Core and Multi Core Circular Sheathed Aluminium Cable with Rigid Conductor (V2) as per IS 694, PVC Insulated Unsheathed Cable with Rigid Conductor (V2) ISI Marked To IS 694

Searched String: 50 Sq mm Aluminium Flat thimble (Tube Terminals)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1), Aluminium Conductors For Overhead Transmission Purposes (V2) Conforming To IS 398

Searched String: 70 Sq mm Aluminium Flat thimble (Tube Terminals)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1)

Searched String: 95 Sq mm Aluminium Flat thimble (Tube Terminals)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1)

Searched String: 120 sq mm Aluminium Flat thimble (Tube Terminals)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1), Terminal Ends for Aluminium Conductors of Insulated Cables (Compression Cable Lugs) Conforming To IS 8309

Searched String: 150 sq mm Aluminium Flat thimble (Tube Terminals)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1), Terminal Ends for Aluminium Conductors of Insulated Cables (Compression Cable Lugs) Conforming To IS 8309, Aluminium Conductors For Overhead Transmission Purposes (V2) Conforming To IS 398

Searched String: 185 sq mm Aluminium Flat thimble (Tube Terminals)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1)

Searched String: 240 sq mm Aluminium Flat thimble (Tube Terminals)

विड विवरण/Bid Details
PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1)

Searched String: 300 sq mm Aluminium Flat thimble (Tube Terminals)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1), Terminal Ends for Aluminium Conductors of Insulated Cables (Compression Cable Lugs) Conforming To IS 8309

Searched String: 400 sq mm Aluminium Flat thimble (Tube Terminals)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1)

Searched String: 16 Sq mm Aluminium Ferrule (In line connector)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1)

Searched String: 25 Sq mm Aluminium Ferrule (In line connector)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1), PVC Single Core and Multi Core Circular Sheathed Aluminium Cable with Rigid Conductor (V2) as per IS 694, PVC Insulated Unsheathed Cable with Rigid Conductor (V2) ISI Marked To IS 694

Searched String: 35 Sq mm Aluminium Ferrule (In line connector)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1)

Searched String: 50 Sq mm Aluminium Ferrule (In line connector)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1), Aluminium Conductors For Overhead Transmission Purposes (V2) Conforming To IS 398

Searched String: 70 Sq mm Aluminium Ferrule (In line connector)

PVC Insulated (Heavy Duty) Electric Cables (V2) as per IS 1554 (Part 1)

Searched String: 70 watt Flood Light, powder coated pressure die cast aluminium body with built in or separate driver as per the requirement with Driver efficiency >85%, Input voltage: 140-270 Volt AC, frequency 50/60 hz, Operating temp range -5 °C to 50 °C, internal surge protection of 5 KV L,N,E as per IEC 61000-4-5, Driver efficiency >85%, THD< 10% as per IEC 61000-3-2 , P. F.≥0.95, IP-66, IK-10, CRI ≥70 , under voltage and over voltage protection, EMI-EMC as per CISPR-15, lenses for beam angle 30 deg-120deg as per the application and the project requirement, suitable tilt able fitting, life time (LED, Driver & electrical circuitary) of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM (Standard Deviation Color Matching) <5, Maximum power

बिड विवरण / Bid Details

consumption should not more than the specified rating and Fixture shall be of relevant BIS standard with Minimum 5 year OEM warranty. System lumen efficacy ≥ 120 and < 135 lm/Watt output . LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted.. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal anagement: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C).

Category not available on GeM for the text string uploaded by the buyer

Searched String: 150 watt Flood Light, powder coated pressure die cast aluminium body with built in or separate driver as per the requirement with Driver efficiency $> 85\%$, Input voltage: 140-270 Volt AC, frequency 50/60 hz, Operating temp range -5 °C to 50 °C, internal surge protection of 5 KV L,N,E as per IEC 61000-4-5, Driver efficiency $> 85\%$, THD $< 10\%$ as per IEC 61000-3-2 , P. F. ≥ 0.95 , IP-66, IK-10, CRI ≥ 70 , under voltage and over voltage protection, EMI-EMC as per CISPR-15, lenses for beam angle 30 deg-120deg as per the application and the project requirement, suitable tilt able fitting, life time (LED, Driver & electrical circuitary) of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM (Standard Deviation Color Matching) < 5 , Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard with Minimum 5 year OEM warranty. System lumen efficacy ≥ 120 and < 135 lm/Watt output . LM79 & LM80 Test report and all testing required for LED fixtures as per BIS shall be submitted.. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal anagement: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C).

Category not available on GeM for the text string uploaded by the buyer

Searched String: 45 watt Street light LED fixture powder coated pressure die cast aluminium body with driver as per the requirement with Driver efficiency $> 85\%$, Input voltage: 140-270 Volt AC, frequency 50/60 hz, Operating temp range -5 °C to 50 °C, internal surge protection of 5 KV L,N,E as per IEC 61000-4-5, Driver efficiency $> 85\%$, THD $< 10\%$ as per IEC 61000- 3-2 , P. F. ≥ 0.95 , IP-66, IK-10, CRI ≥ 70 , under voltage and over voltage protection, EMI-EMC As per CISPR 15 , lenses for beam angle as per IESNA type I/II/III as per the width of the road and the project requirement., suitable to fit in up to 65mm dia pipe, life time (LED,Driver & electrical circuitary) of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM(Standard Deviation Color Matching) < 5 , Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard with Minimum 5 year OEM warranty. System lumen efficacy ≥ 120 < 135 lm/Watt output . LM79 & LM80 and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium

बिड विवरण / Bid Details

housing such that LED junction temperature shall not rise above 90°C).

Category not available on GeM for the text string uploaded by the buyer

Searched String: 72 watt Street light LED fixture powder coated pressure die cast aluminium body with driver as per the requirement with Driver efficiency >85%, Input voltage: 140-270 Volt AC, frequency 50/60 hz, Operating temp range -5 °C to 50 °C, internal surge protection of 5 KV L,N,E as per IEC 61000-4-5, Driver efficiency >85%, THD < 10% as per IEC 61000- 3-2 , P. F.≥0.95, IP-66, IK-10, CRI ≥70, under voltage and over voltage protection, EMI-EMC As per CISPR 15 , lenses for beam angle as per IESNA type I/II/III as per the width of the road and the project requirement., suitable to fit in up to 65mm dia pipe, life time (LED,Driver & electrical circuitary) of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM(Standard Deviation Color Matching) <5, Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard with Minimum 5 year OEM warranty. System lumen efficacy ≥120 <135 lm/Watt output . LM79 & LM80 and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C).

Category not available on GeM for the text string uploaded by the buyer

Searched String: 90 watt Street light LED fixture powder coated pressure die cast aluminium body with driver as per the requirement with Driver efficiency >85%, Input voltage: 140-270 Volt AC, frequency 50/60 hz, Operating temp range -5 °C to 50 °C, internal surge protection of 5 KV L,N,E as per IEC 61000-4-5, Driver efficiency >85%, THD < 10% as per IEC 61000- 3-2 , P. F.≥0.95, IP-66, IK-10, CRI ≥70, under voltage and over voltage protection, EMI-EMC As per CISPR 15 , lenses for beam angle as per IESNA type I/II/III as per the width of the road and the project requirement., suitable to fit in up to 65mm dia pipe, life time (LED,Driver & electrical circuitary) of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM(Standard Deviation Color Matching) <5, Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard with Minimum 5 year OEM warranty. System lumen efficacy ≥120 <135 lm/Watt output . LM79 & LM80 and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C).

Category not available on GeM for the text string uploaded by the buyer

Searched String: 150 watt Street light LED fixture powder

बिड विवरण / Bid Details

coated, pressure die cast aluminium body with driver as per the requirement with Driver efficiency >85%, Input voltage: 140-270 Volt AC, frequency 50/60 hz, Operating temp range -5 °C to 50 °C, internal surge protection of 5 KV L,N,E as per IEC 61000-4-5, Driver efficiency >85%, THD < 10% as per IEC 61000- 3-2 , P. F.≥0.95, IP-66, IK-10, CRI ≥70, under voltage and over voltage protection, EMI-EMC As per CISPR 15 , lenses for beam angle as per IESNA type I/II/III as per the width of the road and the project requirement., suitable to fit in up to 65mm dia pipe, life time (LED,Driver & electrical circuitary) of minimum 50000 Burning Hours with 70% of initial Lumen maintained till life ends as per LM80 extrapolation IES TM-21-11 report, CCT 3000°K / 4000°K / 5700°K /6500°K (As per ANSI Bin), SDCM(Standard Deviation Color Matching) <5, Maximum power consumption should not more than the specified rating and Fixture shall be of relevant BIS standard with Minimum 5 year OEM warranty. System lumen efficacy ≥120 <135 lm/Watt output . LM79 & LM80 and all testing required for LED fixtures as per BIS shall be submitted. Shape size and CCT shall be as approved by Engineer-in-Charge as per requirement. (Thermal management: heat sink of aluminium housing such that LED junction temperature shall not rise above 90°C).

Category not available on GeM for the text string uploaded by the buyer

Searched String: 10 to 11 Watt, 0.6 Metre (nominal size) LED Bollard Light fitting complete with LED module, electronic driver with minimum Surge Voltage protection 3 kV, diffuser, and all other accessories, minimum system luminous efficacy of 80 lm/W and Average life L70B50: 50000 hours, IP65, IK07, Operating voltage range: 140 V - 270 V, the bollard housing should be made up of metallic pipe duly powder coated with the mounting flange at the bottom. The seller shall provide five years manufacturers' warranty for complete luminaire.

Category not available on GeM for the text string uploaded by the buyer

Searched String: 25-watt LED-based post-top luminaire, IP 65, with Die-cast aluminium spigot housing, complete with diffuser, LED module, electronic driver with surge protection of >=10KV, PF >0.9, and all other accessories, having minimum system luminous efficacy of 95 lm/W, operating voltage range: 140 V - 270 V, and average luminaire life L70B50: 50000 hours. The seller shall provide five years manufacturers' warranty for complete luminaire.

Category not available on GeM for the text string uploaded by the buyer

Searched String: 10 Watt to 12 Watt Spike LED light with aluminium housing, IP66 having tiltable feature to throw light in the desired direction.

Category not available on GeM for the text string uploaded by the buyer

Searched String: Straight through cable jointing kit with heat shrinkable kit with ferrules for 1.1 KV grade cable. Size 2 X 16 sq. mm sq. mm 1.1 KV grade cable.

XLPE Cable for Working Voltages up to and Including 1.1 KV

बिड विवरण/Bid Details as per IS 7098 (Part 1)

Searched String: Straight through cable jointing kit with heat shrinkable kit with ferrules for 1.1 KV grade cable. Size 2 X 25 sq. mm sq. mm 1.1 KV grade cable.

XLPE Cable for Working Voltages up to and Including 1.1 KV as per IS 7098 (Part 1)

Searched String: Straight through cable jointing kit with heat shrinkable kit with ferrules for 1.1 KV grade cable. Size 3½ X 35 sq. mm sq. mm 1.1 KV grade cable.

XLPE Cable for Working Voltages up to and Including 1.1 KV as per IS 7098 (Part 1), XLPE Cable, Working Voltage from 3.3 kV up to and including 33 kV (V2) ISI Marked to IS 7098 (Part 2), Cable Joint Kit Suitable for Cables Up to and Including 33 kV (V2)

Searched String: Straight through cable jointing kit with heat shrinkable kit with ferrules for 1.1 KV grade cable. Size 3½ X 300 sq. mm 1.1 KV grade cable.

Cable Joint Kit Suitable for Cables Up to and Including 33 kV (V2)

Searched String: Cable Junction Boxes, IP 66 weather proof, size 205 mm x 255 mm x 112 mm, with terminals suitable for 16 sq mm cable.

Category not available on GeM for the text string uploaded by the buyer

Searched String: 4 Inch Cutting Wheel for Metal suitable for 4" angle grinder.

Metal Oxide Surge Arresters Without Gaps For A.C. Systems (V2) Conforming to IS 15086 (Part 4), Polishing Machines, Desk and Chair Set for Classroom/Training Area, Wild - Life Cages, PLASTIC BIB TAPS, PILLAR TAPS, ANGLE VALVES & STOP VALVES FOR HOT & COLD WATER SERVICES Conforming to IS 9763, Alphabet Block Set / Number Block Set (Preschool Kit), Sign holders or stands, Cable Joint Kit Suitable for Cables Up to and Including 33 kV (V2), Ratchet Pipe Threader for Taper Pipe Threads as per IS 16176, General Purpose Battery Chargers

Searched String: 1.5 Volt Alkaline non-rechargeable, type battery, size- AAA.

Swing Check Type Reflux Valves for Water Works Purposes (Single Door Pattern) (V2) as per IS 5312 (Part1), Sealed Nickel Cadmium Button Type Rechargeable Single Cells Conforming to IS 10893

Searched String: 1.5 Volt Alkaline non-rechargeable, type battery, size- AA.

Swing Check Type Reflux Valves for Water Works Purposes (Single Door Pattern) (V2) as per IS 5312 (Part1), Sealed Nickel Cadmium Button Type Rechargeable Single Cells Conforming to IS 10893

Searched String: 9 Volts Alkaline non-rechargeable Battery

Multipurpose Dry Batteries (Non-Rechargeable) (V3) ISI

बिड विवरण / Bid Details

Marked To IS 8144, Rechargeable LED Bulb (V2), Lithium - Ion Rechargeable Batteries, 48 Volt, for E - Rickshaws (V2)

Searched String: 23A, 12V Alkaline Battery.

V - Belts - Endless V - Belt for Industrial Purposes as per IS 2494, Stationary Valve Regulated Lead Acid Batteries (V3) Conforming To IS 15549, 12 Watt White-LED Based Solar Street Lighting System As Per MNRE Specification, Online UPS (≤ 10 KVA) With Battery Conforming To IS 16242 (Part 1)

Searched String: LED Rope Light, (10 watt/metre or 120 LED per metre) in various colors, IP65 rating, with adapter .

Category not available on GeM for the text string uploaded by the buyer

Searched String: Supplying of Adapter for LED Rope Light.

LED Rope Light (LED Strip Light) Conforming To IS 10322 (Part 5/Section 9) (Under BIS Scheme - II), Led Luminaire For Pit Light (Under BIS Scheme - II), LCR Meter, LED Luminaire For Floodlight Conforming To IS 10322 (Part 5/Section 5) (V3) (Under BIS Scheme - II), LED Luminaire for Flood Light, Flame Proof (V2), LED Portable Miner's Cordless Cap Lamp (V2), LED Luminaire For Road And Street Lights Conforming To IS 10322 (Part 5/Section 3) (V3) (Under BIS Scheme - II), LED Luminaire for High Bay Lighting, Steel Wire Ropes for General Engineering Purpose (V2) Conforming to IS 2266, 7 Watt White-LED Based Solar Street Lighting System As Per MNRE Specification

Searched String: LED Rope Light, (6 W/ Mtr), IP65, Tri-Color. 18 Meter.

Category not available on GeM for the text string uploaded by the buyer

Searched String: Supplying Pidilite WD 40 mechanical contact cleaner in 500 ml can with Straw Spray.

Category not available on GeM for the text string uploaded by the buyer

Searched String: 2 x 16 sq mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade , confirming to IS : 7098 (Part-1) 1988 with upto Date Amendments.

Category not available on GeM for the text string uploaded by the buyer

Searched String: 2 x 25 sq mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade , confirming to IS : 7098 (Part-1) 1988 with upto Date Amendments

Category not available on GeM for the text string uploaded by the buyer

Searched String: 3.5 x 35 sq mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade , confirming to IS : 7098 (Part-1) 1988 with upto Date Amendments

Category not available on GeM for the text string uploaded

बिड विवरण/Bid Details

by the buyer

Searched String: 3.5 x 120 sq mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade , confirming to IS : 7098 (Part-1) 1988 with upto Date Amendments.

Category not available on GeM for the text string uploaded by the buyer

Searched String: 3.5 x 400 sq mm aluminium conductor, XLPE Insulated, PVC sheathed, armoured power cable of 1.1 kV grade , confirming to IS : 7098 (Part-1) 1988 with upto Date Amendments

Category not available on GeM for the text string uploaded by the buyer

Searched String: Socket tester to verify that the wall socket is correctly wired and to check for common faults, such as a missing earth connection, with the following features: LCD display Data hold function Three-hole socket line sequence detection Phase voltage (L-N) measurement Leakage voltage (N-E) measurement RCD (or GFCI) test Socket sequence test Automatic shutdown function Detection of wiring errors Trip time test

Category not available on GeM for the text string uploaded by the buyer

Searched String: M-Seal - Regular epoxy compound.

Gasket sealing Compound, M - Seal as per IS 9197, Hot Applied Sealing Compounds For Joints In Concrete-IS:1834, Trifed Mens Shirt, Classroom Stools

Searched String: Pu Foam Insulation Sealant 750 ml

Auditorium Chair (V2)

Searched String: Distilled Water, 5 Liters

Reagent Grade Distilled water, Bi Double Distillation Water Unit (V2), Molecular Grade Water, Rotary Evaporator, Acephate 50%+ Fipronil 5% Water Dispersible Granules (WDG), Reverse Osmosis based Point of Use Water Treatment System for Drinking Purposes (V3) as per IS 16240, Lyophilizer, Non Carbonated Beverage Dispenser (V2), Environmental Chamber, Water Boiler

Searched String: Weatherproof (IP66) wire connector with plug and socket suitable for 4 sq mm copper cable.

PVC Insulated Copper Cable Single Core and Multi Core Circular Sheathed with Rigid Conductor (V2) ISI Marked To IS 694, XLPE Cable for Working Voltages up to and Including 1.1 KV as per IS 7098 (Part 1), Flat Cable, Copper Conductor with PVC Insulation and Sheathed ISI Marked To IS 694

Searched String: Digital Earth Resistance Tester (KUSAM MECO KM-2030 or equivalent specification

Residual Current Device (RCD) or Earth-leakage circuit breaker (ELCB) Tester

Searched String: PVC Weatherproof, IP65, 8 module MCB DB with DIN rail.

बिड विवरण / Bid Details

Category not available on GeM for the text string uploaded by the buyer

Searched String: Wall-Mounted Voltage Stabilizer, Suitable for 1.5 Ton Split Air Conditioner. The stabilizer shall be wall-mounted type and equipped with the following features: High and Low Voltage Cut-off Protection Thermal Overload Protection Time Delay Relay (TDR) Working Voltage Range: 150 – 285 Volts. Warranty: Minimum 3 years.

Category not available on GeM for the text string uploaded by the buyer

Searched String: Wall-Mounted Voltage Stabilizer, Suitable for 2 Ton Split Air Conditioner. The stabilizer shall be wall-mounted type and equipped with the following features: High and Low Voltage Cut-off Protection Thermal Overload Protection Time Delay Relay (TDR) Working Voltage Range: 150 – 285 Volts. Warranty: Minimum 3 years.

Category not available on GeM for the text string uploaded by the buyer

Searched String: Blue Plastic Crate, 4 Litre Capacity, Size: 300 x 200 x 100 mm, suitable for material storage.

Modular Toilet

Searched String: PVC Weatherproof Switch Box (IP66 Rated) Weatherproof enclosure (IP66), suitable for outdoor use. complete with: One Single Pole Switch, and One 3-pin 16 A Socket Outlet, 240V.

Category not available on GeM for the text string uploaded by the buyer

Searched String: (6 / 16) A Power adaptor with in-built RCD 30 ma

Category not available on GeM for the text string uploaded by the buyer

Searched String: Robustt Caution Tape "3 Inches x 130 Mtr" (Pack of 1) White & Red PVC Material, Barricade tape/Danger/Men at work Barricading Tape, Warning Tape Weather Resistant

Category not available on GeM for the text string uploaded by the buyer

Searched String: Polypropylene Floor Standing Caution Sign Board Type: "Caution Men At Work" message, two-sided floor sign board Size (Nominal) : 62 cm (H) x 30 cm (W) Design: Foldable, floor-standing, double-sided visibility

Category not available on GeM for the text string uploaded by the buyer

Searched String: Stainless Steel Clip for fixing LED batten as per sample provided by department.

Compact Light Weight Stainless Steel Multi Utility Tool (MHA)

Searched String: Waterproof Paint Marker, Suitable for marking on: Metal, plastic, glass, fabric, and similar

बिड विवरण / Bid Details

surfaces, Bullet shaped Acrylic Nib, Line Width Approx. 2.2mm - 2.8 mm, Ink Colour: As per requirement, to be approved by the Engineer-in-Charge. ,

Category not available on GeM for the text string uploaded by the buyer

Searched String: 15A insulated test lead cable with dual-ended insulated crocodile clips, suitable for electrical testing. Set of 5 Pc. (

Category not available on GeM for the text string uploaded by the buyer

Searched String: Plastic Step Stool, Nominal Dimensions: Width - 57 cm, Depth - 54 cm, Height - 60 cm

Category not available on GeM for the text string uploaded by the buyer

Searched String: 30W 220V Round Corded Soldering Iron with LED Worklight . 6 Months Warranty.

Category not available on GeM for the text string uploaded by the buyer

Searched String: Solder Paste Flux Pack -50 gm

Soft Solder - IS 193, Flux Cored Solder Wire as per IS 1921, Mosquito Repellent (V2), Toothpaste (V3) Conforming to IS 6356

Searched String: Lead-Free Soldering Wire, 0.8 mm diameter, suitable for electronic and electrical soldering and component repair. 20-gram pack.

Category not available on GeM for the text string uploaded by the buyer

Searched String: Cleaning Cloth Towels, Material: 100% cotton, Suitable for dirt and surface cleaning in general maintenance, Size: 35 cm x 35 cm (nominal), Soft, absorbent, reusable, and washable (

Category not available on GeM for the text string uploaded by the buyer

Searched String: Microfiber Multi-Purpose Cleaning Wipe, suitable for both dry and wet cleaning of surfaces such as glass, plastic, and metal; nominal size 29.2 cm x 29.2 cm

Trichloroethylene, Technical as per IS 245

Searched String: Contactless Surface Temperature Detector. Suitable for non-contact measurement of surface temperature. Measurement Range: -30 °C to +500 °C (Surface Temperature) Operating Temperature: -5 °C to +50 °C

Category not available on GeM for the text string uploaded by the buyer

Searched String: PVC Plastic Pipe Cutter, Cutting Capacity: Up to 42 mm (maximum),

Pipe Cutter

Searched String: HSS Bi-metal Holesaw Set, 20-64 mm

बिड विवरण / Bid Details	diameter: hole saw sizes: 20, 25, 32, 38, 51, and 64 mm
	<p>Category not available on GeM for the text string uploaded by the buyer</p> <p>Searched String: Plastic Tool Box with Organizer, Height 150 mm, width 190 mm, length 335 mm</p> <p>Corrugated Boxes, Double sided tape</p> <p>Searched String: High carbon steel Shovel with Wooden Handle.</p> <p>Chapati/Dosa Griddle (Tawa), Revolving Chair (V5), mugs stainless steel single double walled with double wall moulded handle, Pruning Shear / Secateur, Wrought carbon Steel And Alloy Steel Pipe Fitting for Moderate And High Temperature Service, Modular Table / Meeting Table / Centre Table (V2), High-end Office Furniture Set (V2), Wooden Display cabinet with Glass Doors, Wooden Shelf / Case / Rack / Credenza / Modular Storage (V2), Adaptor sleeve along with locknut and washer</p> <p>Searched String: Hoe (Powrahs) (Make TATA HOE031 - TP 5 Gold or another make of similar specification, as approved by the Engineer-in-Charge)</p> <p>Category not available on GeM for the text string uploaded by the buyer</p> <p>Searched String: High Tempered Iron Pickaxe (Gaiti) with Wooden Handle. Weight (Approx.) : 1.1 kg</p> <p>Category not available on GeM for the text string uploaded by the buyer</p> <p>Searched String: Aluminium /Aluminium Alloy Self-Supporting Type Tower Ladder (Extendable) Fabricated from aluminium sections of size 66 mm (2 5/8") × 31 mm (1 1/4") × 3 mm (1/8") thick (approx.). Steps are made from 25 mm (1") diameter fluted aluminium pipe, spaced at 300 mm (12") intervals. The ladder is equipped with aluminium casted pulley, sisal/nylon rope, and self-locking pawls to ensure secure and adjustable height operation. Base Support: • Two (2) solid rubber wheels on one side for easy mobility. • Two (2) rubber shoes on the opposite side for ground grip and stability during use. • Includes 50 × 50 × 5 mm MS angle brackets for added sturdiness during operation. Additional Features: Complete with handle, side railing, and a top safety ring to ensure user safety at elevated heights. Dimensions: • Closed Height: 20 ft • Extended Height: 36 ft</p>
अधिसूचना के लिए चयनित प्रासंगिक श्रेणियाँ / Relevant Categories selected for notification	<p>Category not available on GeM for the text string uploaded by the buyer</p> <ul style="list-style-type: none"> • Electric Ceiling Fan (V4) ISI Marked to IS 374 • LED Battery • XLPE Cable for Working Voltages up to and Including 1.1 KV as per IS 7098 (Part 1)
बीओक्यू शीर्षक /BOQ Title	ARM of electrical installation of residential building MMC I Supply of Material
वर्षों के अनुभव एवं टर्नओवर से एमएसई को छूट प्राप्त है / MSE Relaxation for Years Of Experience and Turnover	Yes Complete

बिड विवरण/Bid Details	
स्टार्टअप के लिए अनुभव के वर्षों और टर्नओवर से छूट प्रदान की गई है / Startup Relaxation for Years Of Experience and Turnover	Yes Complete
विक्रेता से मांगे गए दस्तावेज़/ Document required from seller	Certificate (Requested in ATC) *In case any bidder is seeking exemption from Experience / Turnover Criteria, the supporting documents to prove his eligibility for exemption must be uploaded for evaluation by the buyer
क्या आप निविदाकारों द्वारा अपलोड किए गए दस्तावेजों को निविदा में भाग लेने वाले सभी निविदाकारों को दिखाना चाहते हैं? संदर्भ मेनू है/ Do you want to show documents uploaded by bidders to all bidders participated in bid?	Yes (Documents submitted as part of a clarification or representation during the tender/bid process will also be displayed to other participated bidders after log in)
बिड लगाने की समय सीमा स्वतः नहीं बढ़ाने के लिए आवश्यक बिड की संख्या। / Minimum number of bids required to disable automatic bid extension	3
दिनों की संख्या, जिनके लिए बिड लगाने की समय-सीमा बढ़ाई जाएगी। / Number of days for which Bid would be auto-extended	3
ऑटो एक्सटेंशन अधिकतम कितनी बार किया जाना है। / Number of Auto Extension count	2
बिड से रिवर्स नीलामी सक्रिय किया/ Bid to RA enabled	Yes
रिवर्स नीलामी योग्यता नियम/ RA Qualification Rule	50% Lowest Priced Technically Qualified Bidders
बिड का प्रकार/ Type of Bid	Two Packet Bid
प्राथमिक उत्पाद श्रेणी/ Primary product category	1200 mm sweep, BEE 5 star rated, ceiling fan with Brush Less Direct Current Motor.
तकनीकी मूल्यांकन के दौरान तकनीकी स्पष्टीकरण हेतु अनुमत समय / Time allowed for Technical Clarifications during technical evaluation	2 Days
निरीक्षण आवश्यक (सूचीबद्ध निरीक्षण प्राधिकरण /जेम के साथ पूर्व पंजीकृत एजेंसियों द्वारा)/ Inspection Required (By Empanelled Inspection Authority / Agencies pre-registered with GeM)	No
अनुमानित बिड मूल्य / Estimated Bid Value	3701099
मूल्यांकन पद्धति/ Evaluation Method	Total value wise evaluation
मध्यस्थता खंड/ Arbitration Clause	No
सुलह खंड/ Mediation Clause	No

ईएमडी विवरण/EMD Detail

एडवाइजरी बैंक/Advisory Bank	State Bank of India
-----------------------------	---------------------

ईएमडी राशि/EMD Amount	74022
-----------------------	-------

ईपीबीजी विवरण /ePBG Detail

एडवाइजरी बैंक/Advisory Bank	State Bank of India
ईपीबीजी प्रतिशत (%) /ePBG Percentage(%)	3.00
ईपीबीजी की आवश्यक अवधि (माह) /Duration of ePBG required (Months).	7

(a). जेम की शर्तों के अनुसार ईएमडी छूट के इच्छुक बिडर को संबंधित कटेगरी के लिए बिड के साथ वैध समर्थित दस्तावेज प्रस्तुत करने है। एमएसई कटेगरी के अंतर्गत केवल वस्तुओं के लिए विनिर्माता तथा सेवाओं के लिए सेवा प्रदाता ईएमडी से छूट के पात्र हैं। व्यापारियों को इस नीति के दायरे से बाहर रखा गया है।/EMD EXEMPTION: The bidder seeking EMD exemption, must submit the valid supporting document for the relevant category as per GeM GTC with the bid. Under MSE category, only manufacturers for goods and Service Providers for Services are eligible for exemption from EMD. Traders are excluded from the purview of this Policy.

(b). ईएमडी और संपादन जमानत राशि, जहां यह लागू होती है, लाभार्थी के पक्ष में होनी चाहिए। / EMD & Performance security should be in favour of Beneficiary, wherever it is applicable.

लाभार्थी /Beneficiary :

PAO HQ NSG NEW DELHI

Directorate General, Central Armed Police Forces, National Security Guard (NSG), Ministry of Home Affairs
(Pao Hq Nsg New Delhi)

बोली विभाजन लागू नहीं किया गया/ Bid splitting not applied.

एमआईआई खरीद वरीयता / MII Purchase Preference

एमआईआई खरीद वरीयता / MII Purchase Preference	Yes
मेक इन इंडिया विक्रेताओं को खरीद में प्राथमिकता, यदि उनका मूल्य L1+X% तक की सीमा में है / Purchase Preference to MII sellers available upto price within L1+X%	20
मेक इन इंडिया खरीद में प्राथमिकता के लिए बिड की मात्रा का अधिकतम प्रतिशत / Maximum Percentage of Bid quantity for MII purchase preference	50
सार्वजनिक खरीद (मेक-इन-इंडिया को प्राथमिकता) आदेश 2017 के अनुसार केवल क्लास 1/क्लास 2 के स्थानीय आपूर्तिकर्ताओं को ही भागीदारी की अनुमति है दिनांक 16.09.2020 (समय-समय पर संशोधित एवं लागू) / Allow participation only from Class 1/Class 2 local suppliers as per the Public procurement(Preference to Make-in-india) order 2017 date 16.09.2020(as amended and applicable time to time)	Yes, in compliance with the MII ORDER : DPIIT Order(as amended and applicable time to time)

एमएसई खरीद वरीयता/MSE Purchase Preference

एमएसई खरीद वरीयता/MSE Purchase Preference	Yes
सूक्ष्म और लघु उद्यम मूल उपकरण निर्माताओं को खरीद में प्राथमिकता, यदि उनका मूल्य L1+X% तक की सीमा में हो / Purchase Preference to MSE OEMs available upto price within L1+X%	15
सूक्ष्म और लघु उद्यम को खरीद में प्राथमिकता के लिए बिड की मात्रा का अधिकतम प्रतिशत / Maximum Percentage of Bid quantity for MSE purchase preference	25

1. If the bidder is a Micro or Small Enterprise as per latest orders issued by Ministry of MSME, the bidder shall be relaxed from the eligibility criteria of "Experience Criteria" as defined above subject to meeting of quality and technical specifications. The bidder seeking Relaxation from Experience Criteria, shall upload the supporting documents to prove his eligibility for Relaxation.

2. If the bidder is a Micro or Small Enterprise (MSE) as per latest orders issued by Ministry of MSME, the bidder shall be relaxed from the eligibility criteria of "Bidder Turnover" as defined above subject to meeting of quality and technical specifications. If the bidder itself is MSE OEM of the offered products, it would be relaxed from the "OEM Average Turnover" criteria also subject to meeting of quality and technical specifications. The bidder seeking Relaxation from Turnover, shall upload the supporting documents to prove his eligibility for Relaxation.

3. If the bidder is a DPIIT registered Startup, the bidder shall be relaxed from the the eligibility criteria of "Experience Criteria" as defined above subject to their meeting of quality and technical specifications. The bidder seeking Relaxation from Experience Criteria, shall upload the supporting documents to prove his eligibility for Relaxation.

4. If the bidder is a DPIIT registered Startup, the bidder shall be relaxed from the the eligibility criteria of "Bidder Turnover" as defined above subject to their meeting of quality and technical specifications. If the bidder is DPIIT Registered OEM of the offered products, it would be relaxed from the "OEM Average Turnover" criteria also subject to meeting of quality and technical specifications. The bidder seeking Relaxation from Turnover shall upload the supporting documents to prove his eligibility for Relaxation.

5. Preference to Make In India products (For bids < 200 Crore):Preference shall be given to Class 1 local supplier as defined in public procurement (Preference to Make in India), Order 2017 as amended from time to time and its subsequent Orders/Notifications issued by concerned Nodal Ministry for specific Goods/Products. The minimum local content to qualify as a Class 1 local supplier is denoted in the bid document. If the bidder wants to avail the Purchase preference, the bidder must upload a certificate from the OEM regarding the percentage of the local content and the details of locations at which the local value addition is made along with their bid, failing which no purchase preference shall be granted. In case the bid value is more than Rs 10 Crore, the declaration relating to percentage of local content shall be certified by the statutory auditor or cost auditor, if the OEM is a company and by a practicing cost accountant or a chartered accountant for OEMs other than companies as per the Public Procurement (preference to Make-in -India) order 2017 dated 04.06.2020. Only Class-I and Class-II Local suppliers as per MII order dated 4.6.2020 will be eligible to bid. Non - Local suppliers as per MII order dated 04.06.2020 are not eligible to participate. However, eligible micro and small enterprises will be allowed to participate .The buyers are advised to refer the OM No.F.1/4/2021-PPD dated 18.05.2023. [OM No.1 4 2021 PPD dated 18.05.2023](#) for compliance of Concurrent application of Public Procurement Policy for Micro and Small Enterprises Order, 2012 and Public Procurement (Preference to Make in India) Order, 2017.

6. Purchase preference will be given to MSEs having valid Udyam Registration and whose credentials are validated online through Udyam Registration portal as defined in Public Procurement Policy for Micro and Small Enterprises (MSEs) Order, 2012 dated 23.03.2012 issued by Ministry of Micro, Small and Medium Enterprises and its subsequent Orders/Notifications issued by concerned Ministry. If the bidder wants to avail themselves of the Purchase preference, the bidder must be the manufacturer / OEM of the offered product on GeM. Traders are excluded from the purview of Public Procurement Policy for Micro and Small Enterprises and hence resellers offering products manufactured by some other OEM are not eligible for any purchase preference. In respect of bid for Services, the bidder must be the Service provider of the offered Service. Relevant documentary evidence in this regard shall be uploaded along with the bid in respect of the offered product or service and Buyer will decide eligibility for purchase preference based on documentary evidence submitted, while evaluating the bid. If L-1 is not an MSE and MSE Seller (s) has / have quoted price within L-1+ 15% (Selected by Buyer) of margin of purchase preference /price band defined in relevant policy, such MSE Seller shall be given opportunity to match L-1 price and contract will be awarded for 25% (selected by Buyer) percentage of total quantity. The buyers are advised to refer the OM No. F.1/4/2021-PPD dated 18.05.2023 [OM No.1 4 2021 PPD dated 18.05.2023](#) for

compliance of Concurrent application of Public Procurement Policy for Micro and Small Enterprises Order, 2012 and Public Procurement (Preference to Make in India) Order, 2017. Benefits of MSE will be allowed only if seller is validated on-line in GeM profile as well as validated and approved by Buyer after evaluation of documents submitted.

7. Estimated Bid Value indicated above is being declared solely for the purpose of guidance on EMD amount and for determining the Eligibility Criteria related to Turn Over, Past Performance and Project / Past Experience etc. This has no relevance or bearing on the price to be quoted by the bidders and is also not going to have any impact on bid participation. Also this is not going to be used as a criteria in determining reasonableness of quoted prices which would be determined by the buyer based on its own assessment of reasonableness and based on competitive prices received in Bid / RA process.

8. Reverse Auction would be conducted amongst first 50% of the technically qualified bidders arranged in the order of prices from lowest to highest. Number of sellers eligible for participating in RA would be rounded off to next higher integer value if number of technically qualified bidders is odd (e.g. if 7 bids are technically qualified, then RA will be conducted amongst L-1 to L-4). In case number of technically qualified bidders are 2 or 3, RA will be between all without any elimination. If Buyer has chosen to split the bid amongst N sellers, then minimum N sellers would be taken to RA round. In case Primary products of only one OEM are left in contention for participation in RA based on lowest 50% bidders qualifying for RA, the number of sellers qualifying for RA would be increased to get at least products of one more OEM (directly participated or through its reseller) if available. Further, if bid(s) of any seller(s) eligible for MSE preference is / are coming within price band of 15% of Non MSE L-1 or if bid of any seller(s) eligible for Make in India preference is / are coming within price band of 20% of non MII L-1, then such MSE / Make in India seller shall also be allowed to participate in the RA process.

PVC Pendent Holder.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

One Way. Bed Switch.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	10	60

Single Pole 10 Amps, Two Way Switch, ISI Marked. Modular Type.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

Modular Bell Push Switch.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	35	60

Modular Blanking Plate.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

Single Pole 25 Amps, One Way Modular Switch, ISI Marked.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

2 Module, Modular Base And Cover Plate.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

3 Module, Modular Base And Cover Plate.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	50	60

4 Module, Modular Base And Cover Plate.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	10	60

6 Module, Modular Base And Cover Plate.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	60	60

12 Module, Modular Base And Cover Plate.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	5	60

Flame Retardant, PVC Electrical Insulation Tapes 6 Mtr X 1.8 Cm Long.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1200	60

PVC Gitt, PVC Rawal Plug, PVC Fastener 38 To 40mm Long.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4000	60

3 Mm Thick Phenolic Laminated Sheet.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	15	60

1.5 Sq. Mm. FRLS Or HFFR Single Core, Multi Strand Copper Conductor, PVC Insulated Cable Suitable Upto 1100 Volts.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4500	60

4.0 Sq. Mm. FRLS Or HFFR Single Core, Multi Strand Copper Conductor, PVC Insulated Cable Suitable Upto 1100 Volts.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	2000	60

6.0 Sq. Mm. FRLS Or HFFR Single Core, Multi Strand Copper Conductor, PVC Insulated Cable Suitable Upto 1100 Volts.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	90	60

Modular MCB Single Pole 25 Amp C Curve, 3 KA Breaking Capacity.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	25	60

Pin Anchor Fastener 6 X 50

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	30	60

Pin Anchor Fastener 8 X 50

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	45	60

Pin Anchor Fastener 8 X 75

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	30	60

Pin Anchor Fastener 10 X 100

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

Ring Hook Fastener M-8

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	5	60

Ring Hook Fastener M-10

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	5	60

Wedge Anchor Fastener 8 Mm X 75 Mm

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	10	60

3 Mm Thick PVC Or Phenolic Laminated Round Sheet Cover Minimum170 Mm Dia For Fan Box.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	30	60

3 Mm Thick PVC Or Phenolic Laminated Round Sheet Cover 100 Mm Dia.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	250	60

3 Module , PVC Surface Modular Box For Following Module.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

6 Module , PVC Surface Modular Box For Following Module.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	30	60

BEE 5 Star Rating, 25 Litres Capacity Water Storage Heater, With Protection Against Over Heating, Multifunction Safety Valve And External Adjustable Thermostat.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

1200 Mm Sweep, BEE 5 Star Rated, Ceiling Fan With Brush Less Direct Current Motor.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	50	60

Supply Of 400 MM, Single Phase Wall Mounting Fan.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	15	60

Fresh Air Fan With Louver Shutter 250 Mm Sweep.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	25	60

230 Mm Sweep, 1400 RPM , Single Phase, Metallic Exhaust Fan Conforming To IS 2312 -1967.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	15	60

Metallic Louvred Shutter Suitable For 300 Mm Sizes Exhaust Fan.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

Metallic Louvred Shutter Suitable For 380 Mm Sizes Exhaust Fan.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	10	60

18- 22 Watt LED Surface Mounted Batten Light.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	800	60

40 Watt LED Surface Mounted Batten Light.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	10	60

5-7 Watt LED Recessed Orsurface Down Lighter.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4	60

12 -15 Watt LED Recessed Or Surface Down Lighter.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	30	60

18 Watt LED Recessed Or Surface Down Lighter.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4	60

LED Batten Emergency ,Inverter, Luminaire Minimum System Lumen Output Of 2000 Lumen.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	5	60

Utility Knife Tapaia UK-3

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4	60

Spare Blade UB-10 For Utility Knife UK-3 Taparia

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

Flexible Connection Pipe 450mm Long, Metal Braided Hoses .

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	50	60

Measuring Tape, Length Of The Tape Is 30 M. The Width Of The Blade Is 13mm.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

Casing Capping Clip

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1000	60

PVC Nail Clip 20 Mm Double Nail.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1000	60

Aluminium Paint .

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4	60

Red Oxide Metal Primer.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4	60

Paint Thinner.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	2	60

Paint Brush 2 Inch

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4	60

Paint Brush 3 Inch

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4	60

Wooden Screw 35 X 8

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	500	60

Wooden Screw 50 X 8

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	200	60

Dry Wall Gypsum Screw 0.75 Inch

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	500	60

Dry Wall Gypsum Screw 1inch

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	500	60

Dry Wall Gypsum Screw 1.5 Inch

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	400	60

10 Amp, 12 Way, PVC Strip Connector.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	25	60

15 Amp, 12 Way, PVC Strip Connector.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	50	60

Iron Drill Bit Set Having 25 Pcs .

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	2	60

Self Supported FRP Platform Step Ladder

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

Multifunction Testers .

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

400 Amp 04 Pole Power Contactor.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	3	60

16 Sq Mm Aluminium Flat Thimble

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	200	60

25 Sq Mm Aluminium Flat Thimble

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	250	60

50 Sq Mm Aluminium Flat Thimble

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	300	60

70 Sq Mm Aluminium Flat Thimble

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	50	60

95 Sq Mm Aluminium Flat Thimble

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	30	60

120 Sq Mm Aluminium Flat Thimble

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	50	60

150 Sqmm Aluminium Flat Thimble

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	30	60

185 Sq Mm Aluminium Flat Thimble

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	30	60

240 Sq Mm Aluminium Flat Thimble

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	60	60

300 Sq Mm Aluminium Flat Thimble

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

400 Sq Mm Aluminium Flat Thimble

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	30	60

16 Sq Mm Aluminium Ferrule

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	200	60

25 Sq Mm Aluminium Ferrule

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	150	60

35 Sq Mm Aluminium Ferrule

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	300	60

50 Sq Mm Aluminium Ferrule

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	300	60

70 Sq Mm Aluminium Ferrule

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	50	60

70 Watt Flood Light, Powder Coated Pressure Die Cast Aluminium Body With Driver .

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	10	60

150 Watt Flood Light, Powder Coated Pressure Die Cast Aluminium Body With Driver.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	3	60

45 Watt Street Light LED Fixture Powder Coated Pressure Die Cast Aluminium Body With Driver .

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	40	60

72 Watt Street Light LED Fixture Powder Coated Pressure Die Cast Aluminium Body With Driver.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	15	60

90 Watt Street Light LED Fixture Powder Coated Pressure Die Cast Aluminium Body With Driver.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	10	60

150 Watt Street Light LED Fixture Powder Coated Pressure Die Cast Aluminium Body With Driver As Per The Requirement With Driver.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local

Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	5	60

10 To 11 Watt, 0.6 Metre Nominal Size LED Bollard Light Fitting Complete With LED Module.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	12	60

25-watt LED-based Post-top Luminaire, IP 65, With Die-cast Aluminium Spigot Housing, Complete With Diffuser, LED Module, Driver With Surge Protection .

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	15	60

10 Watt To 12 Watt Spike LED Light With Aluminium Housing, IP66 Having Tilttable Feature To Throw Light In The Desired Direction.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	15	60

Straight Through Cable Jointing Kit With Heat Shrinkable Kit With Ferrules For 1.1 KV

Grade Cable. Size 2 X 16 Sq. Mm Sq. Mm 1.1 KV Grade Cable.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	3	60

Straight Through Cable Jointing Kit With Heat Shrinkable Kit With Ferrules For 1.1 KV Grade Cable. Size 2 X 25 Sq. Mm Sq. Mm 1.1 KV Grade Cable.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	3	60

Straight Through Cable Jointing Kit With Heat Shrinkable Kit With Ferrules For 1.1 KV Grade Cable. Size 3.5 X 35 Sq. Mm Sq. Mm 1.1 KV Grade Cable.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	5	60

Straight Through Cable Jointing Kit With Heat Shrinkable Kit With Ferrules For 1.1 KV Grade Cable. Size 3.5 X 300 Sq. Mm 1.1 KV Grade Cable.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
-------------------	---------------------------------------------------------------	-------------	------------------	---------------------------------

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	2	60

Cable Junction Boxes, IP 66 Weather Proof, Size 205 Mm X 255 Mm X 112 Mm, With Terminals Suitable For 16 Sq Mm Cable.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	5	60

4 Inch Cutting Wheel For Metal Suitable For 4 Inch Angle Grinder.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	100	60

1.5 Volt Alkaline Non-rechargeable, Type Battery, Size- AAA.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

1.5 Volt Alkaline Non-rechargeable, Type Battery, Size- AA.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

9 Volts Alkaline Non-rechargeable Battery.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	10	60

23A, 12V Alkaline Battery.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4	60

LED Rope Light, 10 Watt Per Metre Or 120 LED Per Metre, In Various Colors, IP65 Rating, With Adopter.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	200	60

Supplying Of Adapter For LED Rope Light.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	10	60

LED Rope Light, 6 W Per Mtr, IP65, Tri-Color. 18 Meter.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	2	60

Supplying Pidilite WD 40 Mechanical Contact Cleaner In 500 MI Can With Straw Spray.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	10	60

2 X 16 Sq Mm Aluminium Conductor, XLPE Insulated, PVC Sheathed, Armoured Power Cable Of 1.1 KV Grade , Confirming To IS 7098 Part 1 1988 With Upto Date Amendments.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	500	60

2 X 25 Sq Mm Aluminium Conductor, XLPE Insulated, PVC Sheathed, Armoured Power Cable Of 1.1 KV Grade , Confirming To IS 7098 Part 1 1988 With Upto Date Amendments.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	500	60

3.5 X 35 Sq. Mm Aluminium Conductor, XLPE Insulated, PVC Sheathed, Armoured Power Cable Of 1.1 KV Grade, Confirming To IS 7098 Part 1 1988 With Up To Date Amendments.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1000	60

3.5 X 120 Sq. Mm Aluminium Conductor, XLPE Insulated, PVC Sheathed, Armoured Power Cable Of 1.1 KV Grade, Confirming To IS 7098 Part 1 1988 With Up To Date Amendments.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	700	60

3.5 X 400 Sq. Mm Aluminium Conductor, XLPE Insulated, PVC Sheathed, Armoured Power Cable Of 1.1 KV Grade, Confirming To IS 7098 Part 1 1988 With Up To Date Amendments.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	100	60

Socket Tester To Verify That The Wall Socket Is Correctly Wired And To Check For Common Faults.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

M-Seal - Regular Epoxy Compound.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4	60

Pu Foam Insulation Sealant 750 MI

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	2	60

Distilled Water, 5 Liters .

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	10	60

Weatherproof, IP66, Wire Connector With Plug And Socket Suitable For 4 Sq Mm Copper Cable.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
-------------------------------	---------------------------

[BOQ Detail Document](#)[View File](#)

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	20	60

Digital Earth Resistance Tester.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

[Specification Document](#)[View File](#)[BOQ Detail Document](#)[View File](#)

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

PVC Weatherproof, IP65, 8 Module MCB DB With DIN Rail.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

[Specification Document](#)[View File](#)

BOQ Detail Document[View File](#)

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

Wall-Mounted Voltage Stabilizer, Suitable For 1.5 Ton Split Air Conditioner.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document[View File](#)**BOQ Detail Document**[View File](#)

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

Wall-Mounted Voltage Stabilizer, Suitable For 2 Ton Split Air Conditioner.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document[View File](#)

[BOQ Detail Document](#)[View File](#)

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परिषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परिषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

Blue Plastic Crate, 4 Litre Capacity, Size 300 X 200 X 100 Mm, Suitable For Material Storage.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

[Specification Document](#)[View File](#)[BOQ Detail Document](#)[View File](#)

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परिषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परिषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4	60

PVC Weatherproof Switch Box, IP66 Rated.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	4	60

A Power Adaptor With In Built RCD 30 Ma

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	2	60

Robustt Caution Tape 3 Inches X 130 Mt, Pack Of 1, White And Red PVC Material, Barricade Tape.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	2	60

Polypropylene Floor Standing Caution Sign Board

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	10	60

Stainless Steel Clip For Fixing LED Batten As Per Sample Provided By Department.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	100	60

Waterproof Paint Marke.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	5	60

15A Insulated Test Lead Cable With Dual-ended Insulated Crocodile Clips, Suitable For Electrical Testing. Set Of 5 Pc.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	2	60

Plastic Step Stool, Nominal Dimensions Width 57 Cm, Depth 54 Cm, Height 60 Cm.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

30W 220V Round Corded Soldering Iron With LED Worklight . 6 Months Warranty.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

Solder Paste Flux Pack -50 Gm

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	2	60

Lead-Free Soldering Wire, 0.8 Mm Diameter, Suitable For Electronic And Electrical Soldering And Component Repair. 20-gram Pack.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	2	60

Cleaning Cloth Towels, Material 100 Percent Cotton.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	28	60

Microfiber Multi-Purpose Cleaning Wipe.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	16	60

Contactless Surface Temperature Detector.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

PVC Plastic Pipe Cutter, Cutting Capacity Up To 42 Mm

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

HSS Bi-metal Holesaw Set, 20 TO 64 Mm Diameter Hole Saw Sizes 20, 25, 32, 38, 51, And 64 Mm.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

Plastic Tool Box With Organizer, Height 150 Mm, Width 190 Mm, Length 335 Mm

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

High Carbon Steel Shovel With Wooden Handle.

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

Hoe Powrahs

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

High Tempered Iron Pickaxe

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

Aluminium Self Supporting Type Tower Ladder Extendable

(क्रमशः श्रेणी 1 और श्रेणी 2 के स्थानीय आपूर्तिकर्ता के रूप में अर्हता प्राप्त करने के लिए आवश्यक/Minimum 50% and 20% Local Content required for qualifying as Class 1 and Class 2 Local Supplier respectively)

तकनीकी विशिष्टियाँ /Technical Specifications

Specification Document	View File
BOQ Detail Document	View File

Advisory-Please refer attached BOQ document for detailed consignee list and delivery period.

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	GURU DATT BHATT	122051,National Security Guards, Manesar	1	60

क्रेता द्वारा जोड़ी गई बिड की विशेष शर्तें/Buyer Added Bid Specific Terms and Conditions

1. Generic

OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 25 percent of bid quantity at the time of placement of contract. The purchaser also reserves the right to increase the ordered quantity up to 25% of the contracted quantity during the currency of the contract at the contracted rates. The delivery period of quantity shall commence from the last date of original delivery order and in cases where option clause is exercised during the extended delivery period the additional time shall commence from the last date of extended delivery period. The additional delivery time shall be $(\text{Increased quantity} \div \text{Original quantity}) \times \text{Original delivery period (in days)}$, subject to minimum of 30 days. If the original delivery period is less than 30 days, the additional time equals the original delivery period. The Purchaser may extend this calculated delivery duration up to the original delivery period while exercising the option clause. Bidders must comply with these terms.

2. Scope of Supply

Scope of supply (Bid price to include all cost components) : Only supply of Goods

3. Certificates

Bidder's offer is liable to be rejected if they don't upload any of the certificates / documents sought in the Bid document, ATC and Corrigendum if any.

4. Forms of EMD and PBG

Bidders can also submit the EMD with Account Payee Demand Draft in favour of

PAO HQ NSG NEW DELHI
payable at
SBI NEW DELHI

Bidder has to upload scanned copy / proof of the DD along with bid and has to ensure delivery of hardcopy to the Buyer within 5 days of Bid End date / Bid Opening date.

5. Forms of EMD and PBG

Bidders can also submit the EMD with Fixed Deposit Receipt made out or pledged in the name of A/C

PAO HQ NSG NEW DELHI

. The bank should certify on it that the deposit can be withdrawn only on the demand or with the sanction of the pledgee. For release of EMD, the FDR will be released in the favour of the bidder by the Buyer after making endorsement on the back of the FDR duly signed and stamped along with covering letter. Bidder has to upload scanned copy/ proof of the FDR along with bid and has to ensure delivery of hardcopy to the Buyer within 5 days of Bid End date/ Bid Opening date

6. **Rate Contract**

Bidder's offer is liable to be rejected if they dont upload any of the certificates / documents sought in the Bid document, ATC and Corrigendum if any.

7. **Generic**

Bidders shall quote only those products (Part of Service delivery) in the bid which are not obsolete in the market and has at least 1 years residual market life i.e. the offered product shall not be declared end-of-life by the OEM before this period.

8. **Buyer Added Bid Specific ATC**

Buyer uploaded ATC document [Click here to view the file.](#)

9. **Generic**

While generating invoice in GeM portal, the seller must upload scanned copy of GST invoice and the screenshot of GST portal confirming payment of GST.

10. **Forms of EMD and PBG**

Successful Bidder can submit the Performance Security in the form of Fixed Deposit Receipt also (besides PBG which is allowed as per GeM GTC). FDR should be made out or pledged in the name of

PAO HQ NSG NEW DELHI

A/C (Name of the Seller). The bank should certify on it that the deposit can be withdrawn only on the demand or with the sanction of the pledgee. For release of Security Deposit, the FDR will be released in favour of bidder by the Buyer after making endorsement on the back of the FDR duly signed and stamped along with covering letter. Successful Bidder has to upload scanned copy of the FDR document in place of PBG and has to ensure delivery of hard copy of Original FDR to the Buyer within 15 days of award of contract.

11. **Sample Clause**

After award of contract – Successful Bidder shall have to get advance sample approved from buyer before bulk manufacturing / starting bulk supplies. Successful Bidder shall submit

5

samples for Buyer's approval, within 5 days of award of contract. Buyer shall, as per contract specifications framework, either approve the advance sample or will provide complete list of modification required in the sample within 5 days of receipt of advance sample. Seller shall be required to ensure supply as per approved sample with modifications as communicated by Buyer. If there is delay from buyer side in approval of advance sample – the delivery period shall be refixed without LD for the period of delay in sample approval. In case, the sample is found to have major deviations / not conforming to the Contract specifications, the buyer at its discretion may call for fresh samples for approval before allowing bulk supplies or may terminate the contract after notifying the deviations to the seller.

Unless otherwise provided in the contract, all samples required for test shall be supplied by the contractor free of cost. Where under the contract, the contractor is required to submit an advance sample, any expenses incurred by the contractor on or in connection with the production of stores in bulk, before the sample has been approved unconditionally shall be borne by the Seller and he shall not claim any compensation in the event of such sample being found unacceptable by the Buyer / Consignee.

12. **Generic**

Actual delivery (and Installation & Commissioning (if covered in scope of supply)) is to be done at following address

MMC-1
CONSTRUCTION SQUADRON
NSG CAMPUS
MANESAR
HARYANA 122051

अस्वीकरण/**Disclaimer**

The additional terms and conditions have been incorporated by the Buyer after approval of the Competent Authority in Buyer Organization, whereby Buyer organization is solely responsible for the impact of these clauses on the bidding process, its outcome, and consequences thereof including any eccentricity / restriction arising in the bidding process due to these ATCs and due to modification of technical specifications and / or terms and conditions governing the bid. If any clause(s) is / are incorporated by the Buyer regarding following, the bid and resultant contracts shall be treated as null and void and such bids may be cancelled by GeM at any stage of bidding process without any notice:-

1. Definition of Class I and Class II suppliers in the bid not in line with the extant Order / Office Memorandum issued by DPIIT in this regard.
2. Seeking EMD submission from bidder(s), including via Additional Terms & Conditions, in contravention to exemption provided to such sellers under GeM GTC.
3. Publishing Custom / BOQ bids for items for which regular GeM categories are available without any Category item bunched with it.
4. Creating BoQ bid for single item.
5. Mentioning specific Brand or Make or Model or Manufacturer or Dealer name.
6. Mandating submission of documents in physical form as a pre-requisite to qualify bidders.
7. Floating / creation of work contracts as Custom Bids in Services.
8. Seeking sample with bid or approval of samples during bid evaluation process. (However, in bids for [attached categories](#), trials are allowed as per approved procurement policy of the buyer nodal Ministries)
9. Mandating foreign / international certifications even in case of existence of Indian Standards without specifying equivalent Indian Certification / standards.
10. Seeking experience from specific organization / department / institute only or from foreign / export experience.
11. Creating bid for items from irrelevant categories.
12. Incorporating any clause against the MSME policy and Preference to Make in India Policy.
13. Reference of conditions published on any external site or reference to external documents/clauses.
14. Asking for any Tender fee / Bid Participation fee / Auction fee in case of Bids / Forward Auction, as the case may be.
15. Buyer added ATC Clauses which are in contravention of clauses defined by buyer in system generated bid template as indicated above in the Bid Details section, EMD Detail, ePBG Detail and MII and MSE Purchase Preference sections of the bid, unless otherwise allowed by GeM GTC.
16. In a category based bid, adding additional items, through buyer added additional scope of work/ additional terms and conditions/or any other document. If buyer needs more items along with the main item, the same must be added through bunching category based items or by bunching custom catalogs or bunching a BoQ with the main category based item, the same must not be done through ATC or Scope of Work.

Further, if any seller has any objection/grievance against these additional clauses or otherwise on any aspect of this bid, they can raise their representation against the same by using the Representation window provided in the bid details field in Seller dashboard after logging in as a seller within 4 days of bid publication on GeM. Buyer is duty bound to reply to all such representations and would not be allowed to open bids if he fails to reply to such representations.

All GeM Sellers/Service Providers shall ensure full compliance with all applicable labour laws,

including the provisions, rules, schemes and guidelines under the four Labour Codes i.e. the Code on Wages, 2019; the Industrial Relations Code, 2020; the Occupational Safety, Health and Working Conditions Code, 2020; and the Code on Social Security, 2020 as and when notified and brought into force by the Government of India.

For all provisions of the Labour Codes that are pending operationalisation through rules, schemes or notifications, the corresponding provisions of the pre-existing labour enactments (such as The Minimum Wages Act, 1948, The Payment of Wages Act, 1936, The Payment of Bonus Act, 1965, The Equal Remuneration Act, 1976, The Payment of Gratuity Act, 1972, etc. and relevant State Rules) shall continue to remain applicable.

The Seller/ Service Providers shall, therefore, be responsible for ensuring compliance under:

- All notified and enforceable provisions of the new Labour Codes as mentioned hereinabove; and
- All operative provisions of the erstwhile Labour Laws until their complete substitution.

All obligations relating to wages, social security, safety, working conditions, industrial relations etc. and any other statutory requirements shall be strictly met by the Seller/ Service Provider. Any non-compliance shall constitute a breach of the contract and shall entitle the Buyer to take appropriate action in accordance with the contract and applicable law.

[यह बिड सामान्य शर्तों के अंतर्गत भी शासित है /This Bid is also governed by the General Terms and Conditions](#)

जेम की सामान्य शर्तों के खंड 26 के संदर्भ में भारत के साथ भूमि सीमा साझा करने वाले देश के बिडर से खरीद पर प्रतिबंध के संबंध में भारत के साथ भूमि सीमा साझा करने वाले देश का कोई भी बिडर इस निविदा में बिड देने के लिए तभी पात्र होगा जब वह बिड देने वाला सक्षम प्राधिकारी के पास पंजीकृत हो। बिड में भाग लेते समय बिडर को इसका अनुपालन करना होगा और कोई भी गलत घोषणा किए जाने व इसका अनुपालन न करने पर अनुबंध को तत्काल समाप्त करने और कानून के अनुसार आगे की कानूनी कार्रवाई का आधार होगा।/In terms of GeM GTC clause 26 regarding Restrictions on procurement from a bidder of a country which shares a land border with India, any bidder from a country which shares a land border with India will be eligible to bid in this tender only if the bidder is registered with the Competent Authority. While participating in bid, Bidder has to undertake compliance of this and any false declaration and non-compliance of this would be a ground for immediate termination of the contract and further legal action in accordance with the laws.

---धन्यवाद/Thank You---